



# 4.4 **Hydrology**

The nearest surface water bodies to the site are the Corrib Estuary which is adjacent to the site and the River Corrib which is located approximately 230 metres to the west of the site. The Corrib Estuary is classed as a transitional waterbody by the EPA.

A review of the EPA Water Framework Directive monitoring database indicates that the Corrib Estuary is classed as been unpolluted and not at risk. The EPA has classed the River Corrib, as having a 'Good' status and not at risk.

The local hydrology is presented on Figure 4-4.

# 4.5 **Designated Sites and Habitats**

In the Republic of Ireland, designated sites include National Heritage Areas (NHAs), Proposed National Heritage Areas (pNHAs), Special Areas of Conservation (SACs), candidate Special Areas of Conservation (cSAC) and Special Protection Areas (SPAs).


The site is adjacent to the Galway Bay Complex SAC, Inner Galway Bay SPA and Galway Bay Complex pNHA. The designated sites are presented on Figure 4-5.


# 4.6 Environmental Regulation

The EPA Map portal was reviewed to provide information on the environmental regulation setting of the surrounding area. There are no Industrial Emissions Licensed facilities, Integrated Pollution Control Sites or Waste facilities within 1.5 kilometres of the site.

## 4.7 Human Receptors

The nearest residential receptors are located at the northern, eastern and south western boundaries of the site.







## PREVIOUS REPORTS

A Quantitative Risk Assessment (QRA) has been produced by RSK<sup>1</sup> Group Plc that relates to a section of the proposed site. Pertinent information relating to the site has been summarised below, however the full report should be referenced to for further detail.

It is understood that the QRA was based on information included in an Environmental Site Assessment (ESA) also produced by RSK in 2009. MKO was not in receipt of the ESA for the purposes of this assessment. It is understood that a ground investigation had been previously undertaken in the former tank area of the site.

- The soil and groundwater results obtained from the RSK investigation were compared to human health screening values for a continued oil use that were derived in-house by RSK.
- Human Health Generic Quantitative Risk Assessment (GQRA)
  - Soil No concentrations of MTBE (methyl tert-butyl ether), BTEX (benzene, toluene, ethylbenzene and xylenes) range compounds or aliphatic or aromatic hydrocarbon fractions exceed the generic soil screening values for human health.
  - The report indicated that the potential risk to off-site workers from the soils is considered acceptable. The report also indicated that given the presence of less volatile Total Petroleum Hydrocarbons fractions the linkage to the nearest off-site residential receptors is considered to be incomplete.
  - Groundwater No concentrations of MTBE, BTEX range compounds or aliphatic or aromatic hydrocarbon fractions exceed the generic groundwater screening values for human health nor the laboratory detection limit. Therefore a linkage to onsite workers, offsite workers and any offsite residents is considered incomplete.

#### Water Environment GQRA

- Risks to the water environment were quantified by comparing the groundwater samples to Interim Guideline Values.
- Groundwater analytical results from all monitoring positions onsite were below the laboratory method detection limit (LMDL), and therefore at levels below the Interim Guideline Values. Thus a linkage to the water environment is considered incomplete.

#### Risks to Utilities

- The GAC for permeation of plastic pipes were exceeded in five of the soil samples tested from the top 1 metre of soil.
- The report concluded that a potential risks exists to the water supply and further investigation is required to determine the level of risk.

#### > Summary of Pollutant Linkages

A potentially complete pollutant linkage has been identified at the site with respect to the permeation of plastic services by hydrocarbons sorbed to shallow soil and also to construction workers associated with direct contact with hydrocarbon impacted soil.

<sup>&</sup>lt;sup>1</sup> RSK Group Plc (July 2009). Site Quantitative Risk Assessment. Texoil Galway Truck Park, Galway, County Galway, Ireland. Report 23132-2(01)



## PRELIMINARY RISK ASSESSMENT

## 6.1 Introduction

Historical contamination of land may present harm to human health and the environment. Currently there is no specific legislation addressing contaminated land in Ireland. Contaminated land issues are dealt with either through the planning process by the imposition of conditions in planning permission or by clean-up orders under the water or waste legislation. The most typical mechanism for the clean-up of land is an application for a clean-up order under Sections 57/58 of the Waste Management Act 1996, as amended. This can be directed to the "holder" of the waste, which can be the current landowner or any persons (such as a previous owner) who released or permitted the release of contaminants on the land. Where contaminated land is creating a risk to the groundwater or surface water, the water pollution legislation can also be used.

This preliminary risk assessment has generally been undertaken in accordance with the Environmental Protection Agency's Code of Practice: Environmental Risk Assessment for Unregulated Waste Disposal Sites and the UK Environment Agency's document Model Procedures for the Management of Land Contamination: Contaminated Land Report No.113 (CLR 11).

The rudimentary principle behind the risk-based approach is the source-pathway-receptor concept which requires the three elements to be present in the consideration of risk. The presence of a risk is therefore not considered when one or more of these elements are absent.

# 6.2 Preliminary conceptual site model

A preliminary conceptual site model has been compiled for the site based on the desk study information to identify the potential sources of contamination and the associated potential pollutant linkages.

## 6.2.1 Potential sources

Potential contamination sources can include current and historical activities both on site and on neighbouring land. The following potential sources have been identified at the site:

On-site Sources – It is anticipated that minimal amounts of contamination would be associated with the current site activities however there is the potential for localised spillages/leakages from the petrol station and vehicles using and parking at the site.

Historical records show that the site was used for oil, coal, waste metal and iron ore storage. The following contaminants could be associated with the site activities:

- Metals (Metal fines and cinders possibly containing arsenic, cadmium, chromium, copper, lead, nickel and zinc).
- Organic Chemicals (Hydrocarbons from storage, use and spillages of lubricating oils, greases, paraffin based solvents and polycyclic aromatic hydrocarbons (PAH), solvents).
- Other Contaminants (Asbestos fibres, ash and fill).

Made Ground/Fill Material – Given the developed nature of the site and the history of site reclamation, it is possible that Made Ground may be present within the site, which represents a source of potential ground contamination. The make-up of these fill materials is unknown, however, it is likely that the fill would be composed of heterogeneous material, which is generally comprised of locally excavated soils and construction rubble.



Ground gas – if any encountered Made Ground/superficial deposits have an appreciable organic content there may be a potential to generate ground gases.

Asbestos – may be present in the buildings and structures on site, and also within underlying Made Ground, due to the age of the site.

Off-site sources – potential historical off site sources include the gas works to the northwest of the site, the railway works to the north of the site, the graveyard to the northwest and the foundry located to the west of the site.

## 6.2.2 Potential receptors and associated pathways

Future site occupants – primarily at risk from direct contact, inhalation or ingestion where soil is exposed and from soil gas/vapour accumulation within buildings, arising from organic estuarine silts and clays and possibly contaminated Made Ground/Fill material, if present.

Construction Workers - primarily at risk from direct contact, inhalation or ingestion of contaminants.

Buildings & structures – buried concrete and services, such as plastic water supply pipes, can be at risk from chemically aggressive ground and hydrocarbon contamination if present. Ground gases and vapours may also accumulate in buildings and structures presenting an explosive or asphyxiation risk.

Vegetation & plants - primarily at risk from uptake phytotoxic contaminants such as copper and zinc.

Controlled waters – groundwater and surface water bodies could be at risk from the infiltration and migration of possible contaminants.

# 6.3 Preliminary qualitative risk assessment

A qualitative risk assessment has been undertaken based on the findings of the Conceptual Site Model and the potential pollutant linkages that may exist at the site in accordance with the UK Environment Agency's Contaminated Land Report (CLR) 11. The risks identified are in accordance with the UK Department for Environment, Food and Rural Affairs (DEFRA) Contaminated Land Report (CLR) 6, site prioritisation and categorisation rating system, which is summarised in Table 6-1 below.

Table 6-1 Risk Rating Terminology

Risk Rating	Description
High Risk	<ul> <li>Contaminants very likely to represent an unacceptable risk to identified targets</li> <li>Site probably not suitable for proposed use.</li> <li>Enforcement action possible.</li> <li>Urgent action required.</li> </ul>
Medium Risk	<ul> <li>Contaminants likely to represent an unacceptable risk to identified targets.</li> <li>Site probably not suitable for proposed use.</li> <li>Action required in the medium term.</li> </ul>
Low Risk	<ul> <li>Contaminants may be present but unlikely to create unacceptable risk to identified targets.</li> <li>Site probably suitable for proposed use.</li> <li>Action unlikely to be needed whilst site remains in current use.</li> </ul>



Risk Rating	Description
Negligible Risk	<ul> <li>If contamination sources are present, they are considered to be minor in nature and extent.</li> <li>Site suitable for proposed use.</li> <li>No further action required.</li> </ul>

Based on the above terminology, an assessment of the risks posed by the potential pollutant linkages at the site is outlined in Table 6-2 below.

Table 6-2 Qualitative Risk Assessment

Source/Medium	Receptor	Potential Exposure Route	Risk Rating
Organic/inorganic contaminants (including PAHs, hydrocarbons, metals,	Current/future site occupants	Direct ingestion of soil & dust, inhalation of particulates & vapours, and dermal contact	Low to medium
asbestos, etc.) within underlying soils/Made Ground, if present	Construction workers	Direct ingestion of soil & dust, inhalation of particulates	Low to medium
	Vegetation & Plants	Root uptake	Low to medium
	Building & Structures	Direct contact with water supply pipes and underground concrete structures	Low to medium
Explosive / asphyxiating gases from underlying soils/Made Ground, if present	Internal building spaces and current/ future occupiers	Migration of gases/vapour through the surface and via permeable soils	Low to medium
Organic/inorganic contaminants within	Local surface water bodies	Lateral migration of contaminants	Medium
underlying soils/Made Ground	Groundwater	Lateral migration of contaminants  Vertical migration of contaminants	Medium
Off-site sources	Ground and groundwater conditions beneath the study site	Lateral migration of contaminants. Vertical migration of contaminants.	Low to medium



# 6.3.1 **Summary**

Based on the findings of the desk study, the anticipated ground conditions and past land uses identified in and around the site, a generally low to medium risk is considered for the identified receptors. This is due to the potential for hydrocarbon and heavy metal contamination associated with the previous uses of the site and the potential for contaminated Made Ground from previous phases of redevelopment and past activities at the site. Asbestos may also be contained within the current site structures and underlying Made Ground.



## 7. CURRENT GROUND INVESTIGATION

## 7.1 Fieldwork

The ground investigation was undertaken from the 28<sup>th</sup> August to the 3<sup>rd</sup> September 2019 and comprised the excavation of twenty four window sampler boreholes (WS-01 to WS-24) to a maximum depth of 4.0mbgl. Gas and groundwater monitoring standpipes were installed in WS-04, WS-09, WS-10, WS-12, WS-14, WS-16, WS-18 and WS-23. The borehole locations were discussed in advance with the client and agreed with the tenants.

In order to obtain samples for laboratory chemical testing and to characterise the near surface ground conditions across the site, the exploratory hole arisings were logged and representatively sampled by a suitably qualified engineer from Ground Investigations Ireland Ltd (GII).

The investigation was undertaken generally in accordance with the requirements set out within BS 5930:2015<sup>2</sup> and BS 10175:2011+A2:2017<sup>3</sup>. A site layout and exploratory hole location plan is presented as Figure 7-1, and a record of the borehole logs outlining the material encountered, samples and field testing undertaken for each exploratory hole is presented in Appendix 3.

# 7.2 **Monitoring**

Monitoring has been undertaken on three occasions on the  $3^{\rm rd}$  September,  $19^{\rm th}$  September and  $4^{\rm th}$  October 2019 to record groundwater levels from the standpipes. Ground gas concentrations were also obtained during the monitoring rounds on the  $19^{\rm th}$  September and  $4^{\rm th}$  October 2019. There was no groundwater encountered in boreholes WS-04, WS-09, WS-10, WS-12, WS-14, WS-16, WS-18 and WS-23 during the monitoring round on the  $19^{\rm th}$  September and therefore no groundwater samples were retrieved for laboratory analysis. Groundwater samples were retrieved from two boreholes that were previously installed at the site by RSK during the visit on the  $19^{\rm th}$  September 2019. Where encountered, the water was tested during sampling for in-situ parameters including pH, temperature and electrical conductivity.

The monitoring records are included in Appendix 4.

# 7.3 Laboratory testing

Representative soil samples were sent to Element Materials Technology (a UKAS and MCERTS accredited laboratory) for chemical testing. The analysis included the following determinants:


- Heavy metals including; antimony, arsenic, barium, cadmium, chromium, copper, lead, mercury, molybdenum, nickel, selenium and zinc;
- > Benzene, toluene, ethylbenzene, xylenes (BTEX) compounds;
- Total Petroleum Hydrocarbons (TPHCWG) and Polycyclic aromatic hydrocarbons (PAHs);
- Polychlorinated biphenyl (PCBs);
- > Total monohydric phenols;
- > Total Organic Carbon;
- Natural Moisture Content; and
- > pH determination.

<sup>&</sup>lt;sup>2</sup> BSI (2015). Code of Practice for Ground Investigations BS 5930:2015. BSI Standards Publication

<sup>&</sup>lt;sup>3</sup> BSI (2017). Investigation of Potentially Contaminated Sites – Code of Practice BS10175:2011+A2:2017. BSI Standards Publication



Groundwater samples were analysed for a similar suite of contaminants, which included hardness ( $CaCO_3$ ) within the results. Samples of Made Ground that were scheduled for laboratory analysis were screened for asbestos. Laboratory testing results are presented in Appendix 5.





# 8. GROUND CONDITIONS

The ground conditions encountered during the MKO ground investigation are summarised in Table 8-1, below.

Table 8-1 Summary of Ground Conditions

Stratum	Depth to Top of Stratum (mbgl)	Typical Thickness (m)
Tarmac and concrete hard-standing	0.0	0.04 to 0.5
Grey brown clayey gravel, sandy gravelly clay, sandy clayey gravel, silty sandy gravelly clay, gravelly clayey sand, gravelly clay or gravel. Gravel is fine to coarse subrounded to subangular with occasional cobbles of granite.  Occasional fragments of plastic, glass, red brick, clinker, slate, concrete, porcelain, and ash.  Abundant shell fragments in WS-09 and WS-13  [MADE GROUND]	0.04 to 0.5	0.2 to 2.6
Grey brown sandy gravelly clay, clayey gravelly sand or sandy clayey gravel.  [POSSIBLE MADE GROUND]	0.8 to 1.0	0.6 to 1.4
Grey brown sandy gravelly silty CLAY, sandy gravelly silty CLAY or sandy gravelly CLAY with occasional subangular to subrounded cobbles of granite and occasional shell fragments.	1.0 to 2.0	1.2 to 2.0
[WS-04 and WS-21 only] [POSSIBLE ESTUARINE SEDIMENTS]		

## 8.1.1 Made Ground

Tarmac or reinforced concrete hardstanding was encountered in all exploratory hole locations and varied in thickness between 0.04m and 0.5 metres, over Made Ground in all exploratory hole locations during the ground investigation. The Made Ground typically ranged in thickness between 0.2 metres and 2.6 metres. The Made Ground generally comprised of a clayey gravel, sandy gravelly clay, sandy clayey gravel, silty sandy gravelly clay, gravelly clayey sand, gravelly clay or gravel.

Obstructions were encountered in window sampler boreholes WS-01 (0.5 metres below ground level (mbgl)), WS-02 (0.5mbgl), WS-03 (0.54mbgl), WS-07 (0.7mbgl), WS-08 (0.5mbgl), WS-11 (0.7mbgl), WS-15 (0.5mbgl), WS-15A (0.4mbgl) and WS-24 (0.5mbgl) and therefore these boreholes were terminated at these depths due to the obstructions.



## 8.1.2 **Possible Estuarine Sediments**

Possible Estuarine Sediments (PED) were encountered in WS-04 and WS-21 only. The material was found to consist of a generally soft to firm sandy gravelly silty clay. The estuarine sediments typically ranged in thickness between 1.2m to 2.0m and it was typically encountered at depths of 1.0m to 2.0m below ground level.

## 8.1.3 **Groundwater**

There were no groundwater encountered in the boreholes during drilling. The groundwater levels in the monitoring standpipes were measured by GII during three monitoring visits. A summary of the groundwater levels is presented in Table 8-2.

Table 8-2 Summary of Groundwater Monitoring Results

Borehole No.	Response Zone	Depth to groundwater (mbgl)					
		03/09/19	19/09/19	04/10/19			
WS-04	Made Ground/PED	1.80	Dry	2.00			
WS-09	Made Ground	Dry	Dry	Dry			
WS-10	Made Ground	Dry	Dry	Dry			
WS-12	Made Ground	Dry	Dry	Dry			
WS-14	Made Ground	Dry	Dry	Dry			
WS-16	Made Ground	Dry	Dry	Dry			
WS-18	Made Ground	2.60	2.63	2.62			
WS-23	Made Ground	Dry	Dry	Dry			
WS-28 (RSK)	Not known	Not recorded	4.58	4.37			
WS-29 (RSK)	Not known	Not recorded	4.43	3.61			

The groundwater flow direction in the Made Ground was not conclusively determined based on site data. There is insufficient data available to conclude whether groundwater exists as a separate waterbody within the Made Ground and whether there is connectivity in the groundwater between the Made Ground and other strata.

# 8.1.4 **Ground gas**

The atmospheric pressures and local pressure system during the two rounds of ground gas monitoring visits are presented in Table 8-3.



Table 8-3 Summary of Ground Gas Monitoring Pressures

Visits	Atmospheric pressure (mb)	Local pressure system
19/09/2019	1030-1032	Falling
04/10/2019	1002-1006	Rising

The main findings of the monitoring are summarised below and further details are provided in Section 9.5:

Table 8-4 Summary of worst case ground gas monitoring records in all boreholes

Borehole	Response Zone	Flow (l/hr)	0 <sub>2</sub> (min %)	CO <sub>2</sub> (max %)	CH4 (max %)
WS-04	Made Ground/PED	<0.1	20.0	0.2	0.3
WS-09	Made Ground	<0.1	19.4	2.0	<0.1
WS-10	Made Ground	<0.1	20.1	0.1	<0.1
WS-12	Made Ground	<0.1	19.2	0.5	0.2
WS-14	Made Ground	<0.1	20.3	0.1	0.2
WS-16	Made Ground	<0.1	20.1	0.1	0.3
WS-18	Made Ground	<0.1	18.3	2.0	0.1
WS-23	Made Ground	<0.1	20.5	0.1	<0.1

# 8.1.5 **Ground Contamination**

No visual or olfactory evidence of contamination was encountered during drilling or site monitoring.



# SOIL CONTAMINATION ASSESSMENT

## 9.1 **Risks to Human Health**

The results of the assessment undertaken on samples of the Made Ground and Possible Estuarine Sediments are set out in Tables 6.2 to 6.5 of Appendix 6. MKO have screened the soil chemical results from the ground investigation against Generic Assessment Criteria (GAC) derived by LQM/CIEH (Suitable 4 Use Levels) for a number of end use scenarios including Residential (without Private Gardens) and Commercial land use scenario. It is noted that the Soil Guideline Value (SGV) for lead has been withdrawn and that the Category 4 Screening Level (C4SL) for lead will be used in its place.

Where the dataset is of appropriate size, assessment against the applicable GAC or is carried out at the 95th percentile of the sample mean (designated US95), which is considered to represent a reasonable worst-case scenario. An assessment of the normality of the data has been undertaken. Where datasets are normally distributed the one sample t-test has been applied to calculate the US95. In the case of nonparametric datasets, the Chebychev Theorem has been applied. The Grubbs Test has also been used to identify potential outliers within datasets.

Thirty one Made Ground samples and four soil samples were tested by Element on behalf of MKO for a range of parameters including heavy metals, Total Petroleum Hydrocarbons, Benzene, toluene, ethylbenzene, xylenes and polycyclic aromatic hydrocarbons. An asbestos screen was also carried out on the thirty five soil samples.

## 9.1.1 Risks from Made Ground

#### 9.1.1.1 Residential without Private Gardens Land Use Scenario

As can be observed from Table 6.2 of Appendix 6, elevated concentrations of lead, benzo(a)pyrene, benzo(b)fluoranthene and dibenzo(a,h)anthracene have been identified within the Made Ground across the site, which pose a risk to human health.

The concentrations of the remaining contaminants analysed are below the assessment criteria and therefore are not considered to present an unacceptable risk to human health based on a residential (without private gardens) land use scenario.

#### 9.1.1.2 Commercial Land Use Scenario

As can be observed from Table 6.3 of Appendix 6, the measured concentrations for the determinants analysed in the Made Ground are below the assessment criteria and therefore are not considered to present an unacceptable risk to human health based on a Commercial land use scenario.

#### 9.1.2 Risks from Natural Ground

#### 9.1.2.1 Residential without Private Gardens Land Use Scenario

As can be observed from Table 6.4 of Appendix 6, the measured concentrations for the determinants analysed in the possible estuarine sediment samples are below the assessment criteria and therefore are not considered to present an unacceptable risk to human health based on a residential (without private gardens) land use scenario.



#### 9.1.2.2 Commercial Land Use Scenario

As can be observed from Table 6.5 of Appendix 6, the measured concentrations for the determinants analysed in the possible estuarine sediment samples are below the assessment criteria and therefore are not considered to present an unacceptable risk to human health based on a Commercial land use scenario.

## 9.2 **Asbestos**

Asbestos containing material (amosite and chrysotile fibre bundles) were identified in the Made Ground samples from window sampler boreholes WS-10 between 1m and 2mbgl and WS-18 between 0m and 2mbgl. There was no asbestos identified in the other window sampler boreholes.

## 9.3 Risks to Plant Growth

The risks to plant growth (i.e. phytotoxicity) have also been assessed for specific contaminants where the limits for phytotoxic effect proposed by BS3882:2015<sup>4</sup> are significantly lower than the health GAC. The results of the assessment are presented in Table 9-1 below.

Table 9-1 Soil Risks to Vegetation and Plants

Determinant	Assessment Criteria	Measured Range (mg/kg)	Concentration > Assessment Criteria (Y/N)
Copper	135	<1.0 to 2,146	Y
Zinc	200	13.0 to 10,741.00	Y
Nickel	75	5.6 to 47.80	N

As can be observed in Table 9-1, the concentrations of copper and zinc in the Made Ground soil material are above those prescribed by BS3882:2015 and therefore pose a risk to vegetation and plant growth. The concentration of nickel are below the criteria and therefore do not pose a risk to vegetation and plant growth.

## 9.4 Risks to Controlled Waters

Chemical test results from the groundwater samples collected from the two RSK boreholes are presented in Table 6.6 of Appendix 6. The results have been compared against Annual Average Environmental Quality Standards (AA-EQS) $^{5,6,7}$  and Groundwater Threshold Values (GTV) $^{8,9,10,11}$ . In the absence of specific AA-EQS and GTV values, EPA interim guideline values (IGV) $^{12}$  have been

<sup>&</sup>lt;sup>4</sup> BSI (2015). Specification for Topsoil BS3882:2015. BSI Standards Publication

<sup>&</sup>lt;sup>5</sup> European Communities Environmental Objectives (Surface Water) Regulations 2009. S.I. No. 272 of 2009

<sup>&</sup>lt;sup>6</sup> European Union Environmental Objectives (Surface Waters) (Amendment) Regulations 2015. S.I. No. 386 of 2015

<sup>&</sup>lt;sup>7</sup> European Union Environmental Objectives (Surface Waters) (Amendment) Regulations 2019. S.I. No. 77 of 2019

<sup>&</sup>lt;sup>8</sup> European Communities Environmental Objectives (Groundwater) Regulations 2010. S.I. No. 9 of 2010

<sup>&</sup>lt;sup>9</sup> European Union Environmental Objectives (Groundwater) (Amendment) Regulations 2016. S.I. No. 366 of 2016

<sup>&</sup>lt;sup>10</sup> European Communities Environmental Objectives (Groundwater) Regulations 2010. S.I. No. 9 of 2010

<sup>&</sup>lt;sup>11</sup> European Union Environmental Objectives (Groundwater) (Amendment) Regulations 2016. S.I. No. 366 of 2016

<sup>&</sup>lt;sup>12</sup> Environment Protection Agency (2003). Towards Setting Guideline Values for the Protection of Groundwater in Ireland. Interim Report



used. The RSK borehole logs were not available for the purposes of this assessment and therefore the response zone is unknown. Therefore, this screening exercise is for information purposes only.

As can be observed from Table 6.6 the contamination concentrations measured in groundwater found in the RSK Boreholes are below the EQS with the exception of total cyanide, benzo(b+k)fluoranthene and fluoranthene.

As can also be observed from Table 6.6, the concentrations of arsenic in one of the samples and sulphate in two samples are above the GTV threshold. The total cyanide and sulphate concentrations was also above the IGV value.

Whilst it is noted that the limits of detection for cadmium, mercury, phenol, polycyclic aromatic hydrocarbons, Total Petroleum Hydrocarbons and benzene exceed the EQS, GTV and IGV in some instances, the chemical test results of the soil samples have not identified significant elevated concentrations of these contaminants and therefore it is not considered that these contaminants are present at concentrations of concern in the groundwater.

## 9.5 Ground Gas Assessment

A summary of the maximum recorded ground gas concentrations and flow rates are presented below in Table 9-3. Table 9-3 also presents the calculated gas screening value (GSV) and the associated Risk classification and Characteristic Situation  $^{13}$  to CIRIA  $665^{14}$  based on the results of monitoring undertaken. The GSV for each borehole is based on the product of the greater of the methane (CH<sub>4</sub>) or carbon dioxide (CO<sub>2</sub>) concentration measured and the flow rate recorded in each borehole during the monitoring visits. The corresponding risk categories are outlined within Table 9-2 below.

Table 9-2 Modified Wilson and Card Classification (CIRIA Report 659)

Characteristic Situation	Risk Classification	Gas Screening Value (l/hr)		Typical Source Generation
		Lower boundary	Upper Boundary	
1	Very low risk	0	<0.07	Natural soils with low organic content. "Typical" made-up ground.
2	Low risk	0.07	<0.7	Natural soil, high peat/organic content.
3	Moderate risk	0.7	<3.5	Old landfill, inert waste, flood mineworking.
4	Moderate to high	3.5	<15	Mineworking susceptible to flooding, completed landfill.
5	High risk	15	<70	Unflooded, inactive mineworking with shallow working near surface.
6	Very high risk	>70	N.A	Recent landfill site.

<sup>&</sup>lt;sup>13</sup> Wilson et. al. (2006/2007). Characteristic situations, CIRIA 149

<sup>&</sup>lt;sup>14</sup> Wilson et. al. (2007). Assessing risks posed by hazardous ground gases to building, CIRIA C665



Table 9-3 Summary of worst case ground gas monitoring records in boreholes

Borehole	Response Zone	Flow (l/hr)	0 <sub>2</sub> (min %)	CO <sub>2</sub> (max %)	CH4 (max %)	CO <sub>2</sub> Gas screening value (GSV)	CH <sub>4</sub> Gas screening value (GSV)	Classification CIRIA
WS-04	Made Ground/PED	<0.1	20.0	0.2	0.3	0.0002	0.0003	Characteristic Situation 1
WS-09	Made Ground	<0.1	19.4	2.0	<0.1	0.002	0.0001	Characteristic Situation 1
WS-10	Made Ground	<0.1	20.1	0.1	<0.1	0.0001	0.0001	Characteristic Situation 1
WS-12	Made Ground	<0.1	19.2	0.5	0.2	0.0005	0.0002	Characteristic Situation 1
WS-14	Made Ground	<0.1	20.3	0.1	0.2	0.0001	0.0002	Characteristic Situation 1
WS-16	Made Ground	<0.1	20.1	0.1	0.3	0.0001	0.0003	Characteristic Situation 1
WS-18	Made Ground	<0.1	18.3	2.0	0.1	0.002	0.0001	Characteristic Situation 1
WS-23	Made Ground	<0.1	20.5	0.1	<0.1	0.0001	0.0001	Characteristic Situation 1

CIRIA guidance (C665) recommends that site characterisation of ground gas risk is calculated from the maximum concentrations and flow rates across the site as a whole, taking into consideration the conceptual site model.

The maximum recorded gas concentrations (volume gas/volume air) across the site were recorded as 0.3 v/v% for methane and 2.0 v/v% for carbon dioxide. The maximum flow rate recorded in the monitoring wells was recorded as <0.1 litres/hour (l/hr). The GSV would therefore be 0.0003 l/h for methane and 0.002 l/h for carbon dioxide. Therefore, currently available monitoring data indicates that the site conforms to Characteristic Situation 1.

## 9.6 Waste Classification

The soil laboratory test results were assessed to evaluate whether the material should be classified as 'hazardous' or 'non-hazardous', in accordance with the Environmental Protection Agency guidance document; 'Waste Classification: List of Waste & Determining if Waste is Hazardous or Non-hazardous (2015)', and in accordance with the guidance in UK Environmental Agency Technical Guidance WM3.

An assessment of the soil for waste classification purposes (see Table 9-5) indicates that of the thirty one Made Ground and four soil samples tested by Element on behalf of MKO, seven samples would be classified as hazardous and twenty eight samples would be classified as not-hazardous (i.e. inert or non-hazardous) for waste recovery/disposal purposes.

As indicated in Section 9.2 asbestos containing material were identified in the Made Ground samples from window sampler boreholes WS-10 between 1m and 2mbgl and WS-18 between 0m and 2mbgl.



Asbestos quantification was subsequently carried on the samples from WS-10 between 1m and 2mbgl and WS-18 between 0m and 2mbgl. The results from the asbestos quantification are presented in Table 9-4 below.

Table 9-4 Asbestos Quantification Results

Location	Asbestos Identification Name	Asbestos Quantification (%)
WS10 1.0-2.0mbgl	Chrysotile fibre bundles	< 0.1%
WS18 0.0-1.0mbgl	Chrysotile fibre bundles	< 0.1%
WS18 1.0-2.0mbgl	Chrysotile, amosite fibre	< 0.1%
	bundles, bitumen products	

The result from the quantification testing indicates that the areas of Made Ground where asbestos was identified in window sampler boreholes WS-10 between 1m and 2mbgl and WS-18 between 0m and 2mbgl were below the hazardous threshold of >0.1% asbestos by weight.

Table 9-5 Summary of Waste Characterisation

	aste Characterisation			
Sample Location	Depth (mbgl)	Stratum	Characterisation <sup>1</sup>	Contaminants
WS-01	0.00-0.50	Made Ground	Not-hazardous	N/A
WS-02	0.00-0.50	Made Ground	Not-hazardous	N/A
WS-03	0.00-0.54	Made Ground	Not-hazardous	N/A
WS-04	0.00-1.00	Made Ground	Not-hazardous	N/A
WS-04	1.00-2.00	Possible Estuarine Sediments	Not-hazardous	N/A
WS-04	2.00-2.20	Possible Estuarine Sediments	Not-hazardous	N/A
WS-05	0.00-1.00	Made Ground	Not-hazardous	N/A
WS-05	1.00-1.70	Made Ground	Not-hazardous	N/A
WS-07	0.00-0.70	Made Ground	Not-hazardous	N/A
WS-09	0.00-1.00	Made Ground	Not-hazardous	N/A
WS-09	1.00-1.50	Made Ground	Not-hazardous	N/A
WS-10	0.00-1.00	Made Ground	Hazardous	Metals
WS-10	1.00-2.00	Made Ground	Hazardous	Metals, <0.1% Asbestos
WS-11	0.00-0.70	Made Ground	Hazardous	Metals
WS-12	0.00-1.00	Made Ground	Not-hazardous	N/A



Sample Location	Depth (mbgl)	Stratum	Characterisation <sup>1</sup>	Contaminants
WS-12	1.00-2.00	Made Ground	Not-hazardous	N/A
WS-13	0.00-1.00	Made Ground	Not-hazardous	N/A
WS-13	1.00-2.00	Made Ground	Not-hazardous	N/A
WS-14	0.00-1.00	Made Ground	Not-hazardous	N/A
WS-16	0.00-1.00	Made Ground	Hazardous	Metals
WS-17	0.00-1.00	Made Ground	Not-hazardous	N/A
WS-18	0.00-1.00	Made Ground	Hazardous	Metals, <0.1% Asbestos
WS-18	1.00-2.00	Made Ground	Hazardous	Metals, TPH, PAH, <0.1% Asbestos
WS-18	2.00-2.80	Made Ground	Hazardous	Metals, TPH, PAH
WS-19	0.00-1.00	Made Ground	Not-hazardous	N/A
WS-19	1.00-1.60	Made Ground	Not-hazardous	N/A
WS-20	0.00-1.00	Made Ground	Not-hazardous	N/A
WS-21	0.00-1.00	Made Ground	Not-hazardous	N/A
WS-21	1.00-2.00	Made Ground	Not-hazardous	N/A
WS-21	2.00-3.00	Possible Estuarine Sediments	Not-hazardous	N/A
WS-21	3.00-4.00	Possible Estuarine Sediments	Not-hazardous	N/A
WS-22	0.00-1.00	Made Ground	Not-hazardous	N/A
WS-23	0.00-1.00	Made Ground	Not-hazardous	N/A
WS-23	1.00-2.00	Made Ground	Not-hazardous	N/A
WS-24	0.00-0.50	Made Ground	Not-hazardous	N/A

Notes

<sup>1.</sup> Not hazardous i.e., inert or non-hazardous



# REFINED RISK ASSESSMENT

# 10.1 Introduction

Further semi-quantitative risk assessment has been undertaken based on the findings of the intrusive investigation and subsequent assessment to evaluate the potential pollutant linkages identified at the site in accordance with Contaminated Land Report (CLR) 11. An assessment of the risks based on the pollutant linkages identified at the site is outlined in Table 10-1 below. A graphical representation of the conceptual site model is included as Figure 10-1.

Table 10-1 Semi-quantitative risk assessment

Source/Medium	Receptor	Potential Exposure Route	Risk Rating	
Organic/inorganic contaminants (including PAHs, hydrocarbons, metals, asbestos, etc.) within underlying soils/Made	Future site occupants	Direct ingestion of soil & dust, inhalation of particulates & vapours, and dermal contact	Medium – where soil is exposed  Negligible/Low – beneath buildings and hard standing	
Ground	Construction workers	Direct ingestion of soil & dust, inhalation of particulates	Low to medium - presence of asbestos and elevated concentrations of lead and PAH recorded within Made Ground.	
	Vegetation & Plants	Root uptake	Medium (due to copper and zinc concentrations identified in the Made Ground).	
	Building & Structures	Direct contact with water supply pipes and underground concrete structures	Low to medium – hydrocarbons present at potential depth of water pipe at two locations.	
Explosive / asphyxiating gases from underlying soils/Made Ground, if present	Internal building spaces and current/ future occupiers	Migration of gases/vapour through the surface and via permeable soils	Low - based on the results of the gas monitoring visits.	
Organic/inorganic contaminants within underlying soils/Made Ground	Local surface water bodies	Lateral migration of contaminants	Low to Medium – Ground investigation inconclusive. Further investigation to address data gaps.	
	Groundwater	Lateral migration of contaminants	Low to Medium – Ground investigation inconclusive.	



Source/Medium	Receptor	Potential Exposure Route	Risk Rating
		Vertical migration of contaminants	Further investigation to address data gaps.
Off-site sources	Ground and groundwater conditions beneath the study site	Lateral migration of contaminants.  Vertical migration of contaminants.	Low to Medium – Ground investigation inconclusive. Further investigation to address data gaps.

## 10.2 Risks to Human Health

For a residential without private gardens end-use, the risk to future site users from contaminants in soil is considered to be low to medium due to the elevated concentrations of lead and PAHs encountered in the Made Ground at the site. It is considered that the potential risks to future users via dermal contact, inhalation and ingestion pathways can be mitigated through the provision of a suitable barrier layer comprising either buildings, hard cover or capping layers in communal landscaping areas which will prevent contact with underlying Made Ground.

Based on the gas monitoring conducted on site, a low risk to future users is associated with the concentrations of methane and carbon dioxide recorded.

The risk to construction workers from contaminants in the soil is considered to be low to medium. There is also considered to be a potential medium risk associated with the potential for asbestos containing material (ACM) to be present within the fabric of the existing buildings. Reference should be made to the asbestos register prior to construction. It is considered that the risk posed to construction workers can be minimised by the use of appropriate health, safety and welfare provisions. These include, but are not limited to good site hygiene and the use of appropriate personal protective equipment (PPE).

# 10.3 Risks to Vegetation and Plants


The risk to vegetation and plants is considered to be medium based on the concentrations of phytotoxic contaminants at the site. The risk to vegetation and plants can be mitigated by the use of capping layers in communal landscaping and importation of clean topsoil and growth medium.

## 10.4 Risks to Controlled Waters

There was insufficient groundwater encountered in the MKO boreholes to obtain samples for laboratory analysis. Two groundwater samples were obtained from the RSK boreholes and tested which showed some exceedances above the EQS and GTV threshold values. However, the RSK borehole logs were not available for this assessment and therefore the response zone in the borehole is unknown. Given the uncertainty regarding these results, it is recommended that further investigation and groundwater monitoring be undertaken at the site.

# 10.5 Risks to Buildings and Structures

The contaminants encountered beneath the site may pose a risk to underground services, particularly water supply pipes. This risk can be mitigated through the use of appropriate pipework material.





# 11. FURTHER INVESTIGATION

## 11.1 Introduction

A preliminary ground investigation was undertaken at the Galway Inner Harbour site by GII on behalf of MKO in August 2019. At the time of the investigation the area to the north of the site (Texaco petrol station and swathe of land) was inaccessible and therefore this section of the site has not been investigated.

In addition, a number of the window sampler boreholes refused at shallow depths within the Made Ground and therefore it will be necessary to undertake further investigation by means of rotary or cable percussive drilling to understand the ground conditions at depth. It will also be necessary to install groundwater monitoring wells in order to characterise and assess the groundwater at depth.

Therefore, the objective of further investigation is to obtain information on the previously inaccessible areas of site, confirm the geotechnical and geo-environmental ground/groundwater conditions at depth and investigate potential anomalies from the preliminary investigation.

# 11.2 **Proposed Further Investigation**

The investigative works below are proposed to quantify the environmental and ground conditions and to confirm the preliminary ground investigation and conceptual model.

- 7 No. rotary core drilling to 20-30mbgl to provide geotechnical and geo-environmental data throughout the soil and rock horizon with in-situ testing, sampling and installation of four monitoring wells.
- Geotechnical and chemical laboratory analysis of representative soil/groundwater samples.
- > Two groundwater sampling visits with gas monitoring, to be followed with two additional gas monitoring visits including recording of groundwater levels.



# 12. PRELIMINARY GEOENVIRONMENTAL RECOMMENDATIONS

## 12.1 Contamination and Remediation

Based on a Residential (without private gardens) end use scenario, elevated concentrations of lead and PAHs were encountered in the Made Ground during the ground investigation. The statistical analysis suggests that this is indicative of possible site-wide lead and PAHs contamination within the Made Ground, and may present a potential risk to human health where soil is exposed. It is considered that the risks presented to the health of future occupants by lead and PAHs can be mitigated by the provision of barrier layers within the development where the soils are to remain. These barrier layers can be comprised of the future development footprint i.e. buildings, tarmac/concrete hardstanding or capping layers in communal landscaping areas (see section 12.1.1).

## 12.1.1 Capping Layers

Proposed areas of communal soft landscaping that overly the existing soils should be provided with suitable topsoil and subsoil to form a capping layer to act as a barrier to the underlying contamination and also to act as a growth medium. The capping layer could comprise either 600mm of imported soil including minimum 150mm topsoil or 450mm imported soil including 150mm topsoil over a geotextile.

# 12.2 Gas protection measures

The result of the gas monitoring undertaken to date correlates to a Characteristic Situation 1, indicating that no gas protection measures are required for future developments at the site.

# 12.3 Underground services

In accordance with current  $UKWIR^{15}$  guidance, the use of barrier pipes for water supply may be required in some areas of the site, to prevent possible permeation of contaminants into drinking water supplies.

## 12.4 Material Management and Waste Classification

It may be prudent to undertake further soil sampling at the site once the extent of the soil excavation is known and in advance of individual phases of development, in order to fully delineate the areas for waste management planning purposes and to reduce disposal costs.

## 12.4.1 Re-use, Recycling and Recovery

In order to minimise the volumes of soils for off-site disposal/recovery, it is prudent to consider material management options prior to waste disposal/recovery. The on-site re-use of uncontaminated excavated materials is excluded from the provisions of the Waste Management Acts when it meets the following criteria:

> The material must be uncontaminated.

<sup>&</sup>lt;sup>15</sup> UK Water Industry Research (2010) Guidance for the selection of water supply pipes to be used in brownfield sites



- The material must not comprise of bricks rubble or other man-made substances or objects.
- It must have been excavated as part of the construction activities and be used on the site from which it was excavated for the purposes of construction.
- The holder of the material must be able to demonstrate that the material will definitely be used. Intention of use is not considered satisfactory.

## 12.4.2 Waste Recovery/Disposal

Where offsite recovery or disposal is required, the available laboratory results indicates that of the thirty one Made Ground and four soil samples tested, seven samples would be classified as hazardous and twenty eight samples would be classified as not-hazardous (i.e. inert or non-hazardous) for waste recovery/disposal purposes.

Waste Acceptance Criteria (WAC) testing was also undertaken on all thirty five soil samples to determine the materials suitability for disposal to landfill. The results of the WAC testing and waste characterisation is presented in Table 12-1 and Figure 12-1.

Table 12-1 Summary of Waste Acceptance Criteria Testing

Sample Location	Depth (mbgl)	Stratum	Characterisation <sup>1</sup>	Landfill Type <sup>2</sup> based on WAC Results
WS-01	0.00-0.50	Made Ground	Not-hazardous	Inert
WS-02	0.00-0.50	Made Ground	Not-hazardous	Inert
WS-03	0.00-0.54	Made Ground	Not-hazardous	Inert
WS-04	0.00-1.00	Made Ground	Not-hazardous	Inert
WS-04	1.00-2.00	Possible Estuarine Sediments	Not-hazardous	Inert
WS-04	2.00-2.20	Possible Estuarine Sediments	Not-hazardous	Inert
WS-05	0.00-1.00	Made Ground	Not-hazardous	Inert
WS-05	1.00-1.70	Made Ground	Not-hazardous	Inert
WS-07	0.00-0.70	Made Ground	Not-hazardous	Non-hazardous
WS-09	0.00-1.00	Made Ground	Not-hazardous	Non-hazardous
WS-09	1.00-1.50	Made Ground	Not-hazardous	Inert
WS-10	0.00-1.00	Made Ground	Hazardous	Hazardous
WS-10	1.00-2.00	Made Ground	Hazardous	Hazardous that accepts asbestos
WS-11	0.00-0.70	Made Ground	Hazardous	Hazardous



Sample Location	Depth (mbgl)	Stratum	Characterisation <sup>1</sup>	Landfill Type <sup>2</sup> based on WAC Results
WS-12	0.00-1.00	Made Ground	Not-hazardous	Inert
WS-12	1.00-2.00	Made Ground	Not-hazardous	Inert
WS-13	0.00-1.00	Made Ground	Not-hazardous	Non-hazardous
WS-13	1.00-2.00	Made Ground	Not-hazardous	Inert
WS-14	0.00-1.00	Made Ground	Not-hazardous	Non-hazardous
WS-16	0.00-1.00	Made Ground	Hazardous	Hazardous
WS-17	0.00-1.00	Made Ground	Not-hazardous	Non-hazardous
WS-18	0.00-1.00	Made Ground	Hazardous	Hazardous that accepts asbestos
WS-18	1.00-2.00	Made Ground	Hazardous	Hazardous that accepts asbestos
WS-18	2.00-2.80	Made Ground	Hazardous	Hazardous
WS-19	0.00-1.00	Made Ground	Not-hazardous	Inert
WS-19	1.00-1.60	Made Ground	Not-hazardous	Inert
WS-20	0.00-1.00	Made Ground	Not-hazardous	Inert
WS-21	0.00-1.00	Made Ground	Not-hazardous	Inert
WS-21	1.00-2.00	Made Ground	Not-hazardous	Inert
WS-21	2.00-3.00	Possible Estuarine Sediments	Not-hazardous	Inert
WS-21	3.00-4.00	Possible Estuarine Sediments	Not-hazardous	Inert
WS-22	0.00-1.00	Made Ground	Not-hazardous	Inert
WS-23	0.00-1.00	Made Ground	Not-hazardous	Non-hazardous
WS-23	1.00-2.00	Made Ground	Not-hazardous	Inert
WS-24	0.00-0.50	Made Ground	Not-hazardous	Non-hazardous

#### Notes


- 1. Not hazardous i.e., inert or non-hazardous
- 2. Non-hazardous i.e. waste which is not classified as hazardous waste.

Please note given the presence of foreign objects in the Made Ground, acceptance at an inert landfill would be subject to confirmation by the selected permitted facility.



It may also be possible to dispose of the non-hazardous material to a licensed soil waste recovery facility, where disposal does not incur landfill tax. This should be discussed with a suitable facility.

All material intended for off-site disposal should be transported and disposed in accordance with the Waste Management Act 1996 and Environmental Protection Agency Act, 1992.





## 12.4.3 Asbestos

Asbestos containing material (amosite and chrysotile fibre bundles) were identified in the Made Ground samples from window sampler boreholes WS-10 between 1m and 2mbgl and WS-18 between 0m and 2mbgl. If this material is to remain on site, a barrier layer, as indicated above, would mitigate the potential risks presented. If excavated, the Made Ground in this area should be stockpiled separately for offsite disposal.

Due to the potential for asbestos containing material within the buildings on-site it is recommended that, if not already available, an asbestos survey is completed prior to any future development at the site.

# 12.5 **Health and Safety**

All site works should be undertaken in accordance with the guidelines prepared by the Safety, Health and Welfare at Work (Construction) Regulations 2013. Works should also be carried out in accordance with the Construction and Environmental Management Plan. During the redevelopment, precautions should be taken to minimise exposure of workers and the general public to potentially harmful substances. Attention should also be paid to restricting possible off-site nuisance such as dust and odour emissions. Such precautions should include, but not be limited to:

- 1. Personal hygiene, washing and changing procedures.
- 2. Adequate personal protective equipment, including, but not limited to, disposable overalls, gloves and particulate filter masks/vapour respirators, where required.
- Measures to avoid surface water ponding and positive collection and disposal of onsite run-off.
- 4. Regular cleaning of site roads, access roads and the public highway including dust suppressions methods (e.g. water spraying), if necessary.
- 5. Waste haulage vehicles should be covered when leaving the site to minimise the release of airborne particulates.





# APPENDIX 1

PHOTOGRAPH RECORDS



Plate 1 - View of transit shed to the rear of the Galway Harbour Office in Area 1




Plate 2 – View of former ice tower building in Area 1



Plate 3 – View of Lasta Mara Steel Fabrication and hardstanding in Area 1




Plate 4 - View of Dun Aengus Dock and scrap metal storage area in Area 2



Plate 5 – View of Contract Car Park in Area 2 (looking west)




Plate 6 – View of Contract Car Park in Area 2 (looking northwest)



Plate 7 – View of fuel storage tanks and bridge access to Galway Harbour Enterprise Park



Plate 8 - View of eastern boundary of site and railway bridge looking north



Plate 9 - View of hardstanding and site office containers in former coal yard site



Plate 10 - View of hardstanding in former coal yard site looking southwest



Plate 11 – View of hardstanding in former oil depot site looking southeast




Plate 12 - View of former oil depot site and Area 4 to the rear looking north








## APPENDIX 2

**HISTORICAL MAPS** 













## APPENDIX 3

**EXPLORATORY HOLE LOGS** 

GROUND	Grou	nd In	vestigations Irel www.gii.ie	Ltd	Site Galway Port	Number WS-01	
Method : D	ech 10 Probing Rig rive-in Windowless ampler	Dimensi		Ground	Level (mOD)	Client  MKO Planning and Environmental Consultants	Job Number 8979-08-19
		Location 530	n 0007.3 E 725070.8 N	Dates 02	/09/2019	Project Contractor Ground Investigations Ireland	Sheet 1/1
Depth (m)	Sample / Tests	Water Depth (m)	Field Records	Level (mOD)	Depth (m) (Thickness)	Description	Legend Nater
0.00-0.50	EN				0.06 - (0.44) - 0.50	TARMACADAM  MADE GROUND: Grey sandy slightly clayey fine to coarse subangular GRAVEL with occasional subangular to subangular cobbles.  Complete at 0.50m	
Remarks Refusal at 0.	.50m due to obstruct	ion.		1	1	Scale (approx)	Logged By
						<b>Figure</b> 8979-08	<b>No.</b> 3-19.WS-01

GROUND IRELAND	Grou	und Investigations Ireland Ltd www.gii.ie			Ltd	Site Galway Port	Number WS-02	
Method : [	Tech 10 Probing Rig Drive-in Windowless Sampler	Dimens		Ground	Level (mOD)	Client  MKO Planning and Environmental Consultants	Job Number 8979-08-19	•
	·	Locatio 53	n 0027.8 E 725052.3 N	Dates 02	2/09/2019	Project Contractor Ground Investigations Ireland	Sheet 1/1	
Depth (m)	Sample / Tests	Water Depth (m)	Field Records	Level (mOD)	Depth (m) (Thickness)	Description	Legend Nate	
Remarks Period at 0	0.50m depth due to ob	petruction			- (0,09) - (0.41) - (0.50	TARMACADAM  MADE GROUND: Grey sandy slightly clayey fine to coarse subangular GRAVEL with occasional subangular to subrounded cobbles.  Complete at 0.50m	Logged	
reiusal at (	som depth due to ob	ວຣແ UC(10N.				(approx) 1:25 Figure	PM	
							8-19.WS-02	

GROUND MYENGANDA IRELAND	Grou	und Investigations Ireland Ltd www.gii.ie			Ltd	Site Galway Port	Number WS-03
Method : [	Tech 10 Probing Rig  Orive-in Windowless  Sampler	Dimens		Ground	Level (mOD)	Client  MKO Planning and Environmental Consultants	Job Number 8979-08-19
		Locatio 53	n 0046.6 E 725038.4 N	Dates 02	2/09/2019	Project Contractor Ground Investigations Ireland	Sheet 1/1
Depth (m)	Sample / Tests	Water Depth (m)	Field Records	Level (mOD)	Depth (m) (Thickness)	Description	Legend Sage
Remarks Control of the Control of th	EN Standarth due to de				(0.08) - (0.46) - 0.54	TARMACADAM  MADE GROUND: Grey sandy slightly clayey fine to coarse subangular GRAVEL with occasional subangular to subrounded cobbles.  Complete at 0.54m	Logged
kerusal at 0	).54m depth due to ob	struction.				Scale (approx)  1:25  Figure 1 8979-08	РМ

Grou	Ground Investigations Ireland Ltd www.gii.ie			Ltd	Site Galway Port			umber /S-04
Machine : Tech 10 Probing Rig Method : Drive-in Windowless Sampler			Ground	Level (mOD)	Client MKO Planning and Environmental Consultants		N	ob umber '9-08-19
	Location 53	on 0039.1 E 725007.6 N	Dates 02	/09/2019	Project Contractor Ground Investigations Ireland		SI	1/1
Depth (m) Sample / Tests	Water Depth (m)	Field Records	Level (mOD)	Depth (m) (Thickness)	Description	Legend	Water	Instr
0.00-1.00 EN  1.00-2.00 EN				(Thickiness) - 0.05 - (0.35) - (0.40 - (0.60) - (1.00) - (1.00) - (2.20 - (2.20 - (3.20) - (3	TARMACADAM  MADE GROUND: Light brown slightly sandy slightly gravelly CLAY with occasional subangular to subrounded cobbles.  MADE GROUND: Grey sandy clayey fine to coarse subangular GRAVEL with occasional subangular to subrounded cobbles  Firm grey slightly sandy slightly gravelly silty CLAY with occasional subangular to subrounded cobbles and occasional shell fragments. Fine to coarse sand and fine to coarse subangular gravel. Some orange mottling.  Firm grey slightly sandy slightly gravelly silty CLAY with occasional subangular to subrounded cobbles of granite.  Complete at 2.20m		M	
Remarks Refusal at 2.20m depth due to	obstruction			- - - - -		Scale (approx)  1:25  Figure N 8979-08	lo.	ogged / PM

Mechanic   Tech 10 Probing Rog   District   Service   Windowess   Windowes	GROUND IRELAND	Ground Investigations Ireland Ltd www.gii.ie			Ltd	Site Galway Port	Number WS-05	
Method   Service   Method   Met	Machine : T	ech 10 Probing Rig	Dimens		Ground	Level (mOD)	Client	Job
Pennase Software at 1.70m depth due to obstruction.    Compare   C	Method : D	Orive-in Windowless Sampler					MKO Planning and Environmental Consultants	
Remarks refuse at 1.70m depth due to obstruction.  Remarks Rem					Dates 02	2/09/2019		
ADD-1.00 EN    Complete at 1.70m depth due to obstruction.   Complet	Depth (m)	Sample / Tests	Water Depth (m)	Field Records	Level (mOD)	Depth (m) (Thickness)	Description	Legend Nate
1:25 PM Figure No.	0.00-1.00  1.00-1.70  Remarks Refusal at 1	EN	struction			- (0.32) - 0.40 - (0.40) - 0.80 - (0.90)	MADE GROUND: Grey sandy slightly clayey fine to coarse subangular GRAVEL with occasional subangular cobbles.  MADE GROUND: Dark brown sandy clayey fine to coarse subangular to subrounded GRAVEL with occasional subangular to subrounded cobbles.  Firm grey slightly sandy slightly gravelly silty CLAY with occasional subangular to subrounded cobbles of granite. (Possible MADE GROUND)	
Figure No.	. Widdel at 1	om dopur due to OL						
8979-08-19.WS-05							Figure	No.

GROUND IRELAND	Ground Investigations Ireland Ltd			Ltd	Site Galway Port	Number	
			www.gii.ie				WS-07
Method : [	ech 10 Probing Rig Orive-in Windowless Sampler	Dimens	ions	Ground	Level (mOD)	Client  MKO Planning and Environmental Consultants	Job Number 8979-08-19
		Locatio	n	Dates	100/0040	Project Contractor	Sheet
		53	0001.1 E 724838.6 N	30	)/08/2019	Ground Investigations Ireland	1/1
Depth (m)	Sample / Tests	Water Depth (m)	Field Records	Level (mOD)	Depth (m) (Thickness)	Description	Nate Page 1
Remarks Refusal at 0	0.70m depth due to ob	ostruction.			. (0.29) . (0.41) . (0.70 . (0	MADE GROUND: Brownish grey sandy clayey fine to coarse subangular to subrounded GRAVEL with occasional subangular to subrounded cobbles.  Complete at 0.70m	
						1:25	PM
						Figure 8979-08	<b>No.</b> 3-19.WS-07

RELAND	Ground Investigations Ireland Ltd www.gii.ie				Ltd	Site Galway Port	Number WS-08	
Method : D	ech 10 Probing Rig rive-in Windowless ampler	Dimensio		Ground	Level (mOD)	Client  MKO Planning and Environmental Consultants	Job Numbe 8979-08	
		Location 5300	029.4 E 724815.8 N	Dates 30	0/08/2019	Project Contractor Ground Investigations Ireland	Sheet 1/1	
Depth (m)	Sample / Tests	Water Depth (m)	Field Records	Level (mOD)	Depth (m) (Thickness)	Description	Legend	Water
					- (0.28) - (0.29) - (0.50) - (	CONCRETE with rebar.  MADE GROUND: Grey slightly sandy slightly clayey fine to coarse subangular to subrounded GRAVEL with occasional subangular to subrounded cobbles.  Complete at 0.50m		
Remarks No environm Refusal at 0.	nental sampling poss 50m depth due to ol	ible. ostruction.				Scale (approx)  1:25  Figure I 8979-08	PM	

GROUND IRELAND	Ground Investigations Ireland Ltd www.gii.ie				Ltd	Site Galway Port			umber
Method : D	ech 10 Probing Rig Drive-in Windowless	Dimensi		Ground	Level (mOD)	Client  MKO Planning and Environmental Consultants		Jo Nu	
J	ampio.	Location 530	1 0105.4 E 724904.9 N	Dates 03	8/09/2019	Project Contractor Ground Investigations Ireland		Sh	1/1
Depth (m)	Sample / Tests	Water Depth (m)	Field Records	Level (mOD)	Depth (m) (Thickness)	Description	Legend	Water	Instr
0.00-1.00  1.00-2.00	EN				0.05 - (0.25) - 0.30 - (0.50) - 0.80 - (0.40) - 1.20 - (0.30) - 1.50	TARMACADAM  MADE GROUND: Grey sandy slightly clayey fine to coarse angular to subrangular GRAVEL with occasional subangular to subrounded cobbles of granite and occasional fragments of plastic and glass. Sand is fine to coarse and gravel is subangular to subrounded.  MADE GROUND: Brown slightly sandy slightly gravelly CLAY with occasional subangular to subrounded cobbles. Abundant shell fragments with occasional fragments of red brick.  MADE GROUND: slightly silty slightly sandy slightly gravelly CLAY with abundant shell fragments.  MADE GROUND: Dark brown slightly sandy slightly gravelly CLAY with occasional subangular to subrounded cobbles and some orange mottling.  Complete at 1.50m			
Remarks Refusal at 1	.50m depth due to ob	ostruction.					Scale (approx) 1:25 Figure N		pgged / PM
							8979-08-		NS-09

GROUND	Ground Investigations Ireland Ltd www.gii.ie				Ltd	Site Galway Port		Number WS-10	
Method : D	ech 10 Probing Rig rive-in Windowless ampler	Dimension		Ground	Level (mOD)	Client MKO Planning and Environmental Consultants			b imber 9-08-19
		Location 530	141.1 E 724856.8 N	Dates 29	/08/2019	Project Contractor Ground Investigations Ireland		Sł	1/1
Depth (m)	Sample / Tests	Water Depth (m)	Field Records	Level (mOD)	Depth (m) (Thickness)	Description	Legend	Water	Instr
1.00-2.00	EN				0.05	TARMACADAM  MADE GROUND: Greyish brown sandy clayey fine to coarse subangular to subrounded GRAVEL with occasional subangular to subrounded cobbles.  MADE GROUND: Dark brownish grey sandy clayey fine to coarse subangular GRAVEL with occasional subangular to subrounded cobbles.  Complete at 2.20m			
Remarks Refusal at 2.	20m depth due to ob	ostruction.			•		Scale (approx) 1:25 Figure N 8979-08	o.	pgged / PM WS-10

GROUND IRELAND	Groui	nd Investigations Ireland Ltd www.gii.ie				Site Galway Port	Number WS-11
Machine : Tech 10  Method : Drive-ir Sample	n Windowless	Dimens		Ground	Level (mOD)	Client  MKO Planning and Environmental Consultants	Job Number 8979-08-19
		Locatio 53	n 0220.7 E 724788.9 N	Dates 03	/09/2019	Project Contractor Ground Investigations Ireland	Sheet 1/1
Depth (m) Sa	mple / Tests	Water Depth (m)	Field Records	Level (mOD)	Depth (m) (Thickness)	Description	Legend Nate
0.00-0.70 EN					- (0.20) - 0.20 - (0.50) - 0.70 - 0.70	MADE GROUND: Brown slightly sandy slightly gravelly CLAY with occasional subangular to subrounded cobbles of granite and occasional fragments of plastic and glass. Sand is fine to coarse and gravel is subangular to subrounded.  Complete at 0.70m	
Refusal at 0.70m o	depth due to ob	struction.				Scale (approx)  1:25  Figure I	РМ

IRELAND A	Ground Investigations Ireland Ltd www.gii.ie				Ltd	Site Galway Port			Number WS-12	
Method : Driv	h 10 Probing Rig ve-in Windowless npler	Dimensio	ons	Ground	Level (mOD)	Client MKO Planning and Environmental Consultants			b umber 9-08-19	
		Location 530	135.2 E 724938.6 N	Dates 29	0/08/2019	Project Contractor Ground Investigations Ireland		Sh	1/1	
Depth (m)	Sample / Tests	Water Depth (m)	Field Records	Level (mOD)	Depth (m) (Thickness)	Description	Legend	Water	Instr	
1.00-2.00	EN				- 0.04 - (0.36) - 0.40 - (0.27) - 0.67 - (0.33) - 1.00 - (0.40) - 1.40 - (0.15) - (0.20) - 1.75 - (0.25) - 2.00	TARMACADAM  MADE GROUND: Grey slightly sandy clayey fine to coarse angular to subangular GRÁVEL.  MADE GROUND: Light brown sandy slightly gravelly clayey SAND with occasional fragments of red brick clinker and concrete.  MADE GROUND: Grey slightly sandy slightly gravelly CLAY with occasional fragments of red brick and clinker.  Brown slightly clayey slightly gravelly fine to coarse SAND with occasional shell fragments. (Possible MADE GROUND)  Brown slightly clayey slightly gravelly fine to coarse SAND with occasional shell fragments. (Possible MADE GROUND)  Firm light brownish grey sandy slightly gravelly CLAY with occasional subangular to subrounded cobbles. (Possible MADE GROUND)  No recovery  Complete at 2.20m				
Remarks Refusal at 2.20	0m depth due to ob	estruction.					Scale (approx)	Lo By	ogged /	
							1:25 Figure N 8979-08	lo.	PM	

GROUND MYERICAND IRELAND	Grou	nd Inv	estigations Ire www.gii.ie	Ltd	Site Galway Port	Number WS-13	
Method : D	ech 10 Probing Rig rive-in Windowless ampler	Dimensi		Ground	Level (mOD)	Client  MKO Planning and Environmental Consultants	Job Number 8979-08-19
		Location 530	183.8 E 724900.9 N	Dates 03	/09/2019	Project Contractor Ground Investigations Ireland	Sheet 1/1
Depth (m)	Sample / Tests	Water Depth (m)	Field Records	Level (mOD)	Depth (m) (Thickness)	Description	Legend Nater
1.00-2.00	EN				0.05 - (0.75) - (0.75) - (0.80) - (0.40) - (0.80) - (0.80) - (0.80) - (0.80) - (0.80) - (0.80)	TARMACADAM  MADE GROUND: Dark brown to grey sandy slightly gravelly CLAY with occasional subangular to subrounded cobbles and occasional fragments of red brick glass and clinker. Fine to coarse sand and fine to coarse subangular to subrounded gravel.  MADE GROUND: Grey slightly silty slightly sandy slightly gravelly CLAY with occasional ocbbles of granite. Abundant shell fragments and occasional fragments of red brick.  MADE GROUND: Brownish grey sandy gravelly CLAY with occasional subangular to subrounded cobbles of granite and occasional fragments of red brick and clinker.  No recovery  Complete at 2.20m	
Remarks Refusal at 2	.20m depth due to ob	estruction.				Scale (approx)  1:25  Figure N 8979-08	PM No. 8-19.WS-13

GROUND	Grou	nd In	vestigations Ire www.gii.ie	land Ltd		Site Galway Port			umber /S-14
Method : D	Tech 10 Probing Rig Orive-in Windowless Sampler	Dimens		Ground	Level (mOD)	Client  MKO Planning and Environmental Consultants		Nı	ob umber 79-08-19
	·	Locatio 53	n 0251.3 E 724864.8 N	Dates 28	3/08/2019	Project Contractor Ground Investigations Ireland		SI	heet 1/1
Depth (m)	Sample / Tests	Water Depth (m)	Field Records	Level Depth (m) (Thickness)		Description	Legend	Water	Instr
Remarks	EN				(0.10) (0.10) (0.25) (0.25) (0.35) (0.35) (0.35) (0.35) (0.35) (0.35) (0.30) (0.30) (0.30) (0.30)	MADE GROUND: Dark grey medium to coarse subangular to subrounded GRAVEL with occasional subangular cobbles.  MADE GROUND: Dark brown sandy clayey fine to coarse subangular to subrounded GRAVEL with occasional subangular to subrounded cobbles.  MADE GROUND: Grey medium to coarse subangular GRAVEL with occasional subangular cobbles.  No recovery  MADE GROUND: Grey fine to coarse sightly sandy slightly clayey GRAVEL with occasional subangular to subrounded cobbles.  Complete at 2.30m			
Refusal at 2	2.30m depth due to ob	ostruction.					Scale (approx) 1:25		pgged y PM
							8979-08		WS-14

RELAND	Grou	nd Inv	vestigations Iro www.gii.ie	eland	Ltd	Site Galway Port	Number WS-15		
Method : D	ech 10 Probing Rig rive-in Windowless ampler	Dimensio		Ground	Level (mOD)	Client  MKO Planning and Environmental Consultants	Job Numb 8979-08	- 1	
		Location 530	173.9 E 724966.3 N	Dates 28 29	5/08/2019- 5/08/2019	Project Contractor Ground Investigations Ireland	Sheet		
Depth (m)	Sample / Tests	Water Depth (m)	Field Records	Level (mOD)	Depth (m) (Thickness)	Description	Legend	Water	
Remarks Refusal at 0 No environm	.50m depth due to ot nental sampling posited 3.00m from initial	ostruction.			(0.10)	CONCRETE with rebar.  MADE GROUND: Brownish grey slightly clayey fine to coarse subangular to subrounded GRAVEL with occasional subangular to subrounded cobbles.  Complete at 0.50m		ed	
WS-15 move	ed 3.00m from initial	planned loo	cation to WS-15A.			1:25 Figure I	PM <b>No.</b> 3-19.WS-		

GROUND	Grou	nd In	vestigations Ire www.gii.ie	land	Ltd	Site Galway Port	Number WS-15A
Method : [	Tech 10 Probing Rig Drive-in Windowless Sampler	Dimens		Ground	Level (mOD)	Client  MKO Planning and Environmental Consultants	Job Number 8979-08-19
		Locatio 53	n 0177.3 E 724966.7 N	<b>Dates</b> 28 29	8/08/2019- 9/08/2019	Project Contractor Ground Investigations Ireland	Sheet 1/1
Depth (m)	Sample / Tests	Water Depth (m)	Field Records	Level (mOD)	Depth (m) (Thickness)	Description	Kater Mater
Remarks Refusal at (No environ)	0.40m depth due to ob mental sampling poss					CONCRETE with rebar.  MADE GROUND: Brownish grey slightly clayey fine to coarse subangular to subrounded GRAVEL with occasional subangular to subrounded cobbles.  Complete at 0.40m	
THO GITVITOTII	circa samping poss					1:25	PM
						Figure 1 8979-08	<b>No.</b> -19.WS-15A

GROUND	Grou	nd In\	estigations Ire	land	Ltd	Site Galway Port	ļ		umber /S-16	
Method : D	ech 10 Probing Rig rive-in Windowless ampler	Dimension	ons	Ground	Level (mOD)	Client MKO Planning and Environmental Consultants			ob umber '9-08-	- 1
		Location 530	1 222.4 E 724935.9 N	Dates 03	3/09/2019	Project Contractor Ground Investigations Ireland		Sh	1/1	
Depth (m)	Sample / Tests	Water Depth (m)	Field Records	Level (mOD) Depth (m) (Thickness)		Description	Legend	Water	Instr	
0.00-1.00	EN				(0.21) - (0.40) - (0.40) - (0.60) - (0.20)	MADE GROUND: Brownish grey sandy slightly clayey fine to coarse subangular GRAVEL with occasional subangular to subrounded cobbles.  MADE GROUND: Brown sandy gravelly CLAY with occasional subangular to subrounded cobbles of granite.  No recovery  MADE GROUND: Grey sandy slightly clayey fine to coarse subangular to subrounded GRAVEL with occasional subangular to subrounded cobbles.  No recovery  Brownish grey sandy slightly clayey fine to coarse subangular to subrounded GRAVEL. (Possible MADE GROUND)  Complete at 2.20m				
Remarks Refusal at 2.	20m depth due to ol	ostruction.		•			Scale (approx)	Lo B)	ogged y	
							1:25		PM	-
							8979-08		WS-16	,

RELAND	Grou	nd Inv	estigations Ire www.gii.ie	Ltd	Site Galway Port	Number WS-17		
Method : D	ech 10 Probing Rig Prive-in Windowless	Dimensio		Ground	Level (mOD)	Client  MKO Planning and Environmental Consultants	Job Number 8979-08-19	
		Location 5302	268.9 E 724902.5 N	Dates 28 29	3/08/2019- 9/08/2019	Project Contractor Ground Investigations Ireland	Sheet 1/1	
Depth (m)	Sample / Tests	Water Depth (m)	Field Records	Level (mOD)	Depth (m) (Thickness)	Description	Legend Nater	
0.00-1.00	EN				(0.53) - (0.53) - (1.04) - (0.43) - (0.53) - (0.53) - (0.53) - (0.53) - (0.53) - (0.53) - (0.53)	MADE GROUND: Brownish grey slightly clayey fine to coarse subangular to subrounded GRAVEL with occasional subangular to subrounded cobbles.  MADE GROUND: Brownish grey slightly clayey fine to coarse subangular to subrounded GRAVEL with occasional subangular to subrounded cobbles.  Complete at 2.53m		
<b>Remarks</b> Refusal at 2	.53m depth due to of	ostruction.			<u> </u>	Scale (approx)  1:25  Figure I 8979-08	PM	

GROUND IRELAND	Grou	nd In	vestigations Ire www.gii.ie	land	Ltd	Site Galway Port			Number WS-18		
Method : D	ech 10 Probing Rig Drive-in Windowless Sampler	Dimens		Ground	Level (mOD)	Client MKO Planning and Environmental Consultants		N	ob umber 79-08-19		
		Locatio 53	n 0205.4 E 725000.2 N		8/08/2019- 9/08/2019	Project Contractor Ground Investigations Ireland		SI	heet 1/1		
Depth (m)	Sample / Tests	Water Depth (m)	Field Records	Level Depth (mOD) (Thickness)		Description	Legend	Water	Instr		
0.00-1.00	EN				(0.19) - (0.19) - 0.19 (0.81)	CONCRETE with rebar.  MADE GROUND: Brownish grey slightly sandy clayey fine to coarse subangular to subrounded GRAVEL with occasional subangular to subrounded cobbles of granite and occasional fragments of red brick.					
1.00-2.00	EN				1.00	MADE GROUND: Dark brown sandy clayey fine to coarse subangular to subrounded GRAVEL with occasional subangular to subrounded cobbles and occasional fragments of glass red brick roof slate and concrete.					
2.00-2.80	EN Constants due to the				2.80 	MADE GROUND: Dark brown sandy gravelly CLAY with occasional subangular to subrounded cobbles. Occasional fragments of red brick ceramics concrete and ash.	Scale		pgged		
neiusal at 2	.80m depth due to ob	วอน นับแปก.					1:25 Figure N 8979-08	lo.	РМ		

GROUND IRELAND	Grou	nd In	vestigations Ire www.gii.ie	land	Ltd	Site Galway Port	Number WS-19		
Method : D	ech 10 Probing Rig Drive-in Windowless	Dimens		Ground	Level (mOD)	Client  MKO Planning and Environmental Consultants	Job Number 8979-08-19		
	,	Locatio 53	n 0239 E 724964.6 N	Dates 03	3/09/2019	Project Contractor Ground Investigations Ireland	Sheet 1/1		
Depth (m)	Sample / Tests	Water Depth (m)	Field Records	Level Depth (m) (Thickness)		Description	Legend Nater		
0.00-1.00	EN EN	(m)			(Thickness)	Brownish grey sandy gravelly CLAY with occasional subangular to subrounded cobbles. (Possible MADE GROUND)  No recovery  Brown slightly sandy gravelly CLAY with occasional subangular to subrounded cobbles of granite. (Possible MADE GROUND)  Complete at 1.60m			
<b>Remarks</b> Refusal at 1	.60m depth due to ob	estruction.				Scale (approx)  1:25  Figure 1 8979-08	PM		

GROUND	Grou	nd Inv	estigations Ire www.gii.ie	land	Ltd	Site Galway Port	Number WS-20
Method : D	ech 10 Probing Rig rive-in Windowless ampler	Dimensio	ns	Ground	Level (mOD)	Client  MKO Planning and Environmental Consultants	Job Number 8979-08-19
		Location 5302	92.8 E 724942.7 N	Dates 29	0/08/2019	Project Contractor Ground Investigations Ireland	Sheet 1/1
Depth (m)	Sample / Tests	Water Depth (m)	Field Records	Level (mOD)	Depth (m) (Thickness)	Description	Legend Nate
0.00-1.00	EN				(0.30) - (0.70) - (0.70) - (0.58) - (0.42) - (0.50) - (0.50) - (0.50)	MADE GROUND: Dark grey sandy clayey fine to coarse subangular GRAVEL with occasional subangular to subrounded cobbles and rare fragments of metal.  MADE GROUND: Dark grey sandy clayey fine to coarse subangular to subrounded GRAVEL with occasional subangular to subrounded cobbles  No recovery  MADE GROUND: Dark grey slightly clayey fine to coarse subangular GRAVEL with occasional subangular cobbles.  Complete at 2.50m	
Remarks Refusal at 2.	50m depth due to ob	ostruction.				Scale (approx	
						1:25 Figure 8979	PM <b>e No.</b> 08-19.WS-20

GROUND IRELAND	Grou	nd Inv	estigations Ire www.gii.ie	eland	Ltd	Site Galway Port	Number WS-21		
Method : D	ech 10 Probing Rig Prive-in Windowless eampler	Dimensio		Ground	Level (mOD)	Client  MKO Planning and Environmental Consultants	Job Number 8979-08-19		
		Location 5302	34.3 E 725038.3 N	Dates 29	9/08/2019	Project Contractor Ground Investigations Ireland	Sheet 1/1		
Depth (m)	Sample / Tests	Water Depth (m)	Field Records	Level (mOD)	Depth (m) (Thickness)	Description	Legend Nater		
0.00-1.00	EN				0.25	CONCRETE  MADE GROUND: Brown slightly sandy slightly gravelly CLAY with occasional subangular to subrounded cobbles of granite.			
1.00-2.00	EN				1.00	MADE GROUND:Brown slightly sandy slightly gravelly CLAY with occasional subangular to subrounded cobbles of granite and occasional fragments of clinker porcelain and shells.			
2.00-3.00	EN		- 1.75 - (0.25) - 2.00 - Tirm light brown slightly sandy slightly gravelly CLAY with occasional subangular to subrounded cobbles of granite and occasional shell fragments.		0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0				
					(0.66) - (0.66) - 2.66	No recovery	0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.0		
3.00-4.00	EN				3.00	Firm to soft light brown slightly sandy slightly gravelly CLAY with occasional subangular to subrounded cobbles of granite.			
	- 3.80 - (0.20) - 4.00 - Complete at 4.00m								
					- - - - - - - - - - -				
Remarks Refusal at 4	.00m depth due to ob	estruction.			<u> </u>	Scale (approx)	Logged By		
						Figure N			

GROUND	Grou	nd Inv	estigations Ire www.gii.ie	Ltd	Site Galway Port	Number WS-22		
Method : D	ech 10 Probing Rig Prive-in Windowless campler	Dimensio		Ground	Level (mOD)	Client  MKO Planning and Environmental Consultants	Job Number 8979-08-19	
		Location 5302	271.4 E 724998.2 N	Dates 29	/08/2019	Project Contractor Ground Investigations Ireland	Sheet 1/1	
Depth (m)	Sample / Tests	Water Depth (m)	Field Records	Level (mOD)	Depth (m) (Thickness)	Description	Nater Water	
Remarks Refusal at 1	.40m depth due to ob	estruction.			(0.25) - 0.25 - 0.30	MADE GROUND: Brownish grey slightly sandy clayey GRAVEL with occasional subangular to subrounded cobbles.  MADE GROUND: Brownish grey slightly sandy clayey fine to coarse subangular to subrounded GRAVEL with occasional subangular to subrounded cobbles of granite.  Complete at 1.40m	Logged	
	, p. 200 to 01					1:25 Figure	РМ	

GROUND IRELAND	Grou	nd Inv	estigations Ire www.gii.ie	eland	and Ltd Site Galway Port					r 3
Method : D	ech 10 Probing Rig Prive-in Windowless	Dimensio		Ground	Level (mOD)	Client  MKO Planning and Environmental Consultants			b umbe 9-08-	- 1
		Location 5303	807.9 E 724987.6 N	Dates 29	0/08/2019	Project Contractor Ground Investigations Ireland		Sh	1/1	
Depth (m)	Sample / Tests	Water Depth (m)	Field Records	Level (mOD)	Depth (m) (Thickness)	Description	Legend	Water	Inst	r
1.00-2.00	EN				(0.23) -	MADE GROUND: Grey sandy slightly clayey fine to coarse subangular to subrounded GRAVEL with occasional subangular to subrounded cobbles.  MADE GROUND: Brown slightly sandy gravelly CLAY with occasional subangular to subrounded cobbles of granite. (Possible MADE GROUND)  No recovery  Grey slightly sandy slightly clayey fine to coarse subangular to subrounded GRAVEL with occasional subangular to subrounded cobbles of granite. (Possible MADE GROUND)  Complete at 2.40m				
Remarks Refusal at 2	.40m depth due to ob	ostruction.					Scale (approx)		gged /	I
							1:25	lo.	PM WO or	
							8979-08-	-19\	NS-23	3

GROUND INVESTIGATIONS IRELAND	Grou	nd In	vestigations Ire www.gii.ie	land	Ltd	Site Galway Port		Number WS-24		
Method : D	ech 10 Probing Rig rive-in Windowless ampler	Dimensi		Ground	Level (mOD)	Client  MKO Planning and Environmental Consultants		Job Number 8979-08-19		
		Location 530	1 0315.4 E 725033.2 N	Dates 02	2/09/2019	Project Contractor Ground Investigations Ireland		Sheet 1/1		
Depth (m)	Sample / Tests	Water Depth (m)	Field Records	Level (mOD) Depth (m) (Thickness)		Description		Legend	*****	
0.00-0.50	EN					CONCRETE with rebar.  MADE GROUND: Brownish grey sandy slightly clayey fir to coarse subangular to subrounded GRAVEL with occasional subangular cobbles.  Complete at 0.50m		Logged		
Refusal at 0.	.50m depth due to ob	estruction.				Sca (appi	25 Jure No	PM o. 19.WS-24	_	





## APPENDIX 4

MONITORING RECORDS



## Ground Investigations Ireland Gas Monitoring Field Sheet

(V1 August 2018)

						•				
			Proje	ct Inforn	nati	ion				
Project Number			8979-08-19			Sample Date			19/09/2019	
Client			МКО			Well I.D.			WS-04	
Site Name			Galway Port			Weather		Dry		
						Weather Previous 24		_		
Sampler I.D.			PM			hours			Dry	
				Well Dat	a	Chanal	aina Tuna uD\	10		
Casing Diameter (mm)			100mm			Standpipe Type uPVC etc.			PVC	
Standpipe Diameter (mm)			50mm			Total Well Depth (m)			2.03	
Stick Up (mm)			Flush			Water Level (mBTOC)			Dry	
Cover Condition			Good			Odour			None	
Gas Meter Model		Ge	Geotech GA 5000			Gas Valve/Cap Condition			In good repair	
				Gas Data	а					
Sample I.D.	Location Type	CH4	CO2	СО	ŀ	H2S	02		rometric ressure	Additional Comment
WS-04		0.3%	0.2%	1ppm	2	ppm	20%	1	.032mb	
		A -l -l:4:			/O.b					

Additional Comments/Observations:



(V1 August 2018)

						•				
			Proje	ct Inforn	nat	ion				
Project Nu	mber		8979-0	08-19		Sa	ample Date		19/0	9/2019
Client	İ		MK	0			Well I.D.		W	'S-09
Site Nar	me		Galway	/ Port			Weather			Dry
Camanlan			DA	4		Weatl	ner Previous 2	24		D
Sampler	Ι.υ.		PN				hours			Dry
				Well Dat	:a	Stand	pipe Type uP\	VC		
Casing Diame	ter (mm)		100r	nm		Staria	etc.	vc	F	PVC
Standpipe Diam	eter (mm)		50m	ım		Total	Well Depth (r	n)	1	65
Stick Up (	mm)		Flus	sh		Water	Level (mBTC	C)		Dry
Cover Cond			God				Odour	•		lone
Gas Meter		Ge	eotech (	GA 5000			s Valve/Cap Condition		In god	od repair
				Gas Data	а					
Sample I.D.	Location Type	CH4	CO2	со		H2S	02		rometric Pressure	Additiona Commen
WS-09	Gas well	0%	2%	3ppm	4	4ppm	19.4%	1	L030mb	



#### (V1 August 2018)

			Pro	ject Infor	mati	ion				
Project Num	nber		8979-	08-19		Sa	ample Date		19/09	9/2019
Client			Mk	(0			Well I.D.		W:	S-10
Site Nam	e		Galwa	y Port			Weather		С	Pry
Sampler I.	D.		PI	M		Weatl	her Previous 2 hours	24		)ry
				Well Da	ata					
Casing Diamete	er (mm)		100	mm	:	Stand	pipe Type uP\ etc.	/C	Р	VC
Standpipe Diame	ter (mm)		50n	nm		Total '	Well Depth (n	n)	2	.18
Stick Up (m	ım)		Flu	sh	,	Water	Level (mBTO	C)	С	ry
Cover Condi	tion		Go	od			Odour		No	one
Gas Meter M	1odel	G	eotech	GA 5000			s Valve/Cap Condition		In goo	d repair
				Gas Da	ta					
Sample I.D.	Location Type	CH4	CO2	СО	Н	I2S	O2	E	Barometric Pressure	Additiona Commen
WS-10	Gas well	0.0%	0.1%	2ppm	4p	pm	20.1%		1030mb	
dditional Commen										



			VI Aug	ust 2016	<u> </u>					
			Proje	ct Inforn	nation	1				
Project Num	ber		8979-0	8-19		Sa	imple Date		19/0	9/2019
Client			МК	0			Well I.D.		W	S-12
Site Name	9		Galway	/ Port			Weather		[	Ory
				_	V	Veath	ner Previous 2	24		
Sampler I.I	D		PN				hours		[	Ory
				Well Dat			aina Tura uD	<i>'</i> C		
Casing Diamete	r (mm)		100n	nm	31	tanap	oipe Type uP\ etc.	/C	F	PVC
Standpipe Diamet	ter (mm)		50m	ım	T	otal \	Well Depth (r	n)	2	.10
Stick Up (m	m)		Flus	sh	W	/ater	Level (mBTO	C)	[	Dry
Cover Condit	tion		God	od			Odour		n	one
Gas Meter M	odel	Ge	eotech (	GA 5000			s Valve/Cap Condition		In god	d repair
				Gas Data	а					
Sample I.D.	Location Type	CH4	CO2	СО	H2	!S	02		rometric ressure	Additional Comment
WS-12	Gas well	0.2%	0.4%	2ppm	4pp	m	19.2%	1	.030mb	
Additional Comment	s/Observati	ons:				Ц				



			V I Aug	ust 2010	<u> </u>					
			Proje	ct Inforn	natior	n				
Project Numl	ber		8979-0	8-19		Sa	imple Date		19/0	9/2019
Client			MK	0			Well I.D.		W	S-14
Site Name	2		Galway	/ Port		,	Weather		I	Ory
				_	٧	Veath	ner Previous 2	24		
Sampler I.D	). 		PN				hours		[	Ory
				Well Dat		بام مرما	-i T	<i>1</i> C		
Casing Diameter	r (mm)		100n	nm	51	tanap	oipe Type uP\ etc.	<i>/</i> C	F	PVC
Standpipe Diamet	er (mm)		50m	ım	Т	otal \	Well Depth (r	n)	2	30
Stick Up (mr	m)		Flus	sh	W	Vater	Level (mBTO	C)	[	Ory
Cover Condit	ion		God	od			Odour		n	one
Gas Meter Mo	odel	Ge	eotech (	GA 5000			s Valve/Cap Condition		In god	od repair
				Gas Data	а					
Sample I.D.	Location Type	CH4	CO2	со	H2	<u>2</u> S	02		rometric ressure	Additional Comment
WS-14	Gas well	0.2%	0.1%	1ppm	Зрр	om	20.3%	1	032mb	
Additional Comments	s/Observati	ons:	ı	1		I.				



#### (V1 August 2018)

		1	Proje	ct Inforn	nation				
Project Nun	nber		8979-0	8-19		Sample Date		19/0	9/2019
Client			MK	0		Well I.D.		W	'S-16
Site Nam	ie		Galway	/ Port		Weather		1	Dry
C l l	5			4	Wea	ather Previous	24		
Sampler I.	.D.		PN.			hours			Dry
				Well Dat		ıdpipe Type uP	N/C		
Casing Diamete	er (mm)		100n	nm	Star	etc.	VC	F	PVC
Standpipe Diame	eter (mm)		50m	ım	Tota	al Well Depth (	m)	2	2.12
Stick Up (m	nm)		Flus	sh	Wat	er Level (mBT0	OC)		Dry
Cover Cond	ition		God	od		Odour		N	lone
				24 5000	(	Gas Valve/Cap			
Gas Meter M	/lodel	Ge		GA 5000 <b>Gas Dat</b>		Condition		In god	od repair
	Location			Gas Dat	<b>d</b>		D a	rometric	Additional
Sample I.D.	Type	CH4	CO2	СО	H2S	O2		ressure	Comment
WS-16	Gas well	0.3%	0.1%	1ppm	3ppm	20.1%	1	L032mb	
1 . 1									



		•	• = / tug	ust 2010						
		1	Proje	ct Inforn	nat	tion		-		
Project Num	ber		8979-0	8-19		Sa	ample Date		19/0	9/2019
Client			MK	0			Well I.D.		W	′S-18
Site Name	e		Galway	/ Port			Weather		1	Dry
				_		Weatl	her Previous	24		
Sampler I.I	D.		PN				hours			Dry
				Well Dat	а	a				
Casing Diamete	er (mm)		100n	nm		Stand	pipe Type uP' etc.	VC	F	PVC
Standpipe Diamet			50m			Total	Well Depth (r	n)		2.72
Stick Up (m			Flus				· Level (mBTC			2.63
Cover Condit			God				Odour	-,		lone
Gas Meter M		Ge		GA 5000			s Valve/Cap Condition			od repair
				Gas Data	а					
Sample I.D.	Location Type	CH4	CO2	со		H2S	02		rometric Pressure	Additional Comment
WS-18	Gas well	0.1%	1.4%	1ppm	3	3ppm	18.9%	1	L032mb	
					_					
Additional Comment	s/Observati	ons:	•	· '						



			Proje	ct Inforn	nat	ion				
Project Num	ber		8979-0	)8-19		Sa	ample Date		19/0	9/2019
Client			MK	0			Well I.D.		W	/S-23
Site Name	9		Galway	/ Port			Weather			Dry
	_			_		Weath	ner Previous 2	24		_
Sampler I.I	).		PN				hours			Dry
			<u>'</u>	Well Dat	a	Ctand	oipe Type uP\	ıc		
Casing Diamete	r (mm)		100n	nm		Stanu	etc.	/C	ſ	PVC
Standpipe Diamet	ter (mm)		50m	ım		Total '	Well Depth (n	n)	2	2.42
Stick Up (m	m)		Flus	sh		Water	Level (mBTO	C)		Dry
Cover Condit	tion		God	od			Odour		N	lone
Gas Meter M	odel	Ge	eotech (	GA 5000			s Valve/Cap Condition		In god	od repair
				Gas Data	3					
Sample I.D.	Location Type	CH4	CO2	СО		H2S	02		rometric ressure	Additional Comment
WS-23	Gas well	0.0%	0.1%	1ppm	***	3ppm	20.5%	1	031mb	
Additional Comments	s/Observation	ns:	1	l						



(V1 August 2018)

			Proje	ct Inforn	nat	ion		-		
Project Nu	mber		8979-0	)8-19		Sa	ample Date		04/1	0/2019
Client	t		MK	0			Well I.D.		W	′S-04
Site Na	me		Galway	/ Port			Weather		١	Vet
Sampler	I D		PN	1		Weatl	her Previous 2 hours	24	,	Vet
Sampler	1.0.			Well Dat			Hours			/vet
				vven Dat	a	Stand	pipe Type uP\	/C		
Casing Diame	ter (mm)		100r	nm			etc.		F	PVC
Standpipe Diam	eter (mm)		50m	ım		Total	Well Depth (n	n)	2	2.03
Stick Up (	mm)		Flus	sh		Water	Level (mBTO	C)	2	2.00
Cover Con	dition		God	od			Odour		N	lone
Gas Meter	Model	G	eotech (	GA 5000			s Valve/Cap Condition		In god	od repair
				Gas Data	а					
Sample I.D.	Location Type	CH4	CO2	со		H2S	02		rometric Pressure	Interna Flow Ra
WS-04	Gas well	0%	0.2%	0ppm	(	Оррт	20.2%	1	L006mb	-0.1 l/ł
										<u> </u>



(V1 August 2018)

			Proje	ct Inforn	nat	ion				
Project Nu	mber		8979-0	08-19		Sa	ample Date		04/1	0/2019
Client	:		MK	0			Well I.D.		W	'S-09
Site Nar	ne		Galway	/ Port			Weather		١	Vet
Sampler	I D		PN	1		Weatl	ner Previous 2 hours	.4	,	Vet
Samplei	1.0.			Well Dat	2		Tiours			WEL
				wen bat	a	Stand	pipe Type uPV	/C		
Casing Diame	ter (mm)		100r	nm			etc.		F	PVC
Standpipe Diam	eter (mm)		50m	ım		Total	Well Depth (n	า)	1	65
Stick Up (	mm)		Flus	sh		Water	Level (mBTO	C)	1	Dry
Cover Con	dition		God	od			Odour		N	one
Gas Meter	Model	G	eotech (	GA 5000			s Valve/Cap Condition		In god	od repair
				Gas Data	<b>a</b>					
Sample I.D.	Location Type	CH4	CO2	со		H2S	02		rometric Pressure	Interna Flow Ra
WS-09	Gas well	0%	0%	1ppm	(	Оррт	21%	1	L006mb	-0.1 l/ł
			1							



(V1 August 2018)

		_	Proje	ct Inforn	nat	ion				
Project Nu	mber		8979-0	)8-19		Sa	ample Date		04/1	0/2019
Client	t		MK	0			Well I.D.		W	'S-10
Site Nar	me		Galway	/ Port			Weather		١	Vet
Sampler	I.D.		PN	1		Weat	her Previous 2 hours	24	١	Vet
				Well Dat	а					
Casing Diame	ter (mm)		100r	nm		Stand	pipe Type uP\ etc.	/C	F	PVC
Standpipe Diam	neter (mm)		50m	ım		Total	Well Depth (n	n)	2	2.15
Stick Up (	mm)		Flus	sh		Water	Level (mBTO	C)	I	Dry
Cover Con	dition		God	od			Odour		N	lone
Gas Meter	Model	G	eotech (	GA 5000			s Valve/Cap Condition		In god	od repair
				Gas Data	3					
Sample I.D.	Location Type	CH4	CO2	СО		H2S	O2		rometric Pressure	Interna Flow Rat
WS-10	Gas well	0%	0%	1ppm	-	0ppm	21%	1	1006mb	-0.0 l/h
		A 1 10.0		mments	/					



(V1 August 2018)

			Proje	ct Inforn	nat	ion				
Project Nu	mber		8979-0	08-19		Sa	ample Date		04/1	0/2019
Client			MK	0			Well I.D.		W	'S-12
Site Nar	ne		Galway	/ Port			Weather		١	Vet
Sampler	l D		PN	1		Weatl	ner Previous 2 hours	24	,	Vet
Samplei	ו.ט.			Well Dat			Hours			vet
				wen bat	a	Stand	pipe Type uPV	/C		
Casing Diamet	ter (mm)		100r	nm			etc.		F	PVC
Standpipe Diam	eter (mm)		50m	ım		Total	Well Depth (n	n)	2	2.10
Stick Up (ı	mm)		Flus	sh		Water	Level (mBTO	C)	1	Dry
Cover Cond	dition		God	od			Odour		N	one
Gas Meter I	Model	G	eotech (	GA 5000			s Valve/Cap Condition		In god	od repair
				Gas Data	а					
Sample I.D.	Location Type	CH4	CO2	со		H2S	02		rometric Pressure	Interna Flow Ra
WS-12	Gas well	0%	0.5%	0ppm	(	Oppm	20.1%	1	L006mb	-0.1 l/h
			1	1						•



(V1 August 2018)

			Proje	ct Inforn	nat	ion				
Project Nu	mber		8979-0	08-19		Sa	ample Date		04/1	0/2019
Client	t		MK	0			Well I.D.		W	'S-14
Site Na	me		Galway	/ Port			Weather		١	Vet
Campler	1.0		PΝ	4		Weatl	ner Previous 2 hours	24	,	Vet
Sampler	ו.ט.			Well Dat			Hours		`	wet
				vveli Dat	a	Stand	pipe Type uP\	/C		
Casing Diame	ter (mm)		100n	nm			etc.		F	PVC
Standpipe Diam	eter (mm)		50m	ım		Total	Well Depth (n	n)	2	2.23
Stick Up (	mm)		Flus	sh		Water	Level (mBTO	C)	1	Dry
Cover Con	dition		God	od			Odour		N	one
Gas Meter	Model	G	eotech (	GA 5000			s Valve/Cap Condition		In god	od repair
				Gas Data	а					
Sample I.D.	Location Type	CH4	CO2	со		H2S	02		rometric Pressure	Interna Flow Ra
WS-14	Gas well	0%	0.1%	1ppm	(	Oppm	20.7%	1	L004mb	-0.0 l/ł
			<b>-</b>							



			Proje	ct Inforn	nat	ion				
Project Nur	nber		8979-0	)8-19		Si	ample Date		04/1	0/2019
Client			MK	0			Well I.D.		W	'S-16
Site Nam	ne		Galway	/ Port			Weather		١	Vet
C l I	5		D.	4		Weat	her Previous 2	24	,	A./ - 1
Sampler I	.D.		PN				hours		\	Vet
				Well Dat	a	Stand	pipe Type uP\	/(		
Casing Diamet	er (mm)		100n	nm		Staria	etc.	, ,	F	PVC
Standpipe Diame	eter (mm)		50m	ım		Total	Well Depth (r	n)	2	2.06
Stick Up (n	nm)		Flus	sh		Water	r Level (mBTO	C)	1	Dry
Cover Cond			God	od			Odour			one
Gas Meter N	Лodel	G	eotech (	GA 5000			ns Valve/Cap Condition		In god	od repair
				Gas Data	а					
Sample I.D.	Location Type	CH4	CO2	СО		H2S	O2		rometric Pressure	Internal Flow Rate
WS-16	Gas well	0%	0.1%	0ppm	(	0ppm	20.2%	1	L002mb	-0.0 l/h
			<u> </u>		<u> </u>					



						,,-	7 tagast = 0 = 0			
			Proje	ct Inforn	nat	ion				
Project Nu	mber		8979-0	)8-19		Sa	ample Date		04/1	.0/2019
Client	t		MK	0			Well I.D.		W	/S-18
Site Nar	me		Galway	/ Port			Weather		١	Wet
6 1				â		Weatl	her Previous 2	24		
Sampler	I.D.		PN				hours		\	Net
				Well Dat	a	Standi	pipe Type uP\	/C		
Casing Diamet	ter (mm)		100r	nm		Staria	etc.		F	PVC
Standpipe Diam	eter (mm)		50m	ım		Total	Well Depth (n	n)	2	2.70
Stick Up (ı	mm)		Flus	sh		Water	Level (mBTO	C)	2	2.62
Cover Cond			God	od			Odour		N	lone
							s Valve/Cap			
Gas Meter I	Model	G	eotech (	GA 5000		(	Condition		In god	od repair
	Location			Gas Data	d			D.	rometric	Interna
Sample I.D.	Type	CH4	CO2	СО		H2S	02		Pressure	Flow Rat
WS-18	Gas well	0%	2%	0ppm	(	0ppm	18.3%	1	L003mb	-0.1 l/h
_										
	1 1	Additi	ional Co	mments	/OI	oservati	ons:			1



						,	7 tagast = 0 = 0			
			Proje	ct Inforn	nat	ion				
Project Nu	mber		8979-0	)8-19		Sa	ample Date		04/1	.0/2019
Client			MK	0			Well I.D.		W	/S-23
Site Nar	ne		Galway	/ Port			Weather		١	Wet
6	. 5			â		Weatl	ner Previous 2	24		
Sampler	I.D.		PN				hours		\	Net
				Well Dat	а	Standi	pipe Type uP\	/C		
Casing Diamet	ter (mm)		100r	nm		Staria	etc.		F	PVC
Standpipe Diam	eter (mm)		50m	ım		Total '	Well Depth (n	n)	2	2.40
Stick Up (ı	mm)		Flus	sh		Water	Level (mBTO	C)		Dry
Cover Cond	dition		God	od			Odour		N	lone
							s Valve/Cap			
Gas Meter I	Model	G	eotech (	GA 5000		(	Condition		In god	od repair
	Lacation		1	Gas Data	а			Da		lintowno
Sample I.D.	Location Type	CH4	CO2	СО		H2S	O2		rometric Pressure	Interna Flow Rat
WS-23	Gas well	0%	0.1%	0ppm	(	Oppm	20.8%	1	L004mb	-0.0 l/h
-										
	ı	Additi	ional Co	mments	/OŁ	oservati	ons:			<u>I</u>



Ground Investigations Ireland Ltd.,
Catherinestown House,
Hazelhatch Road,
Newcastle, Co Dublin.
Tel: 01 601 5175 / 5176 | Fax: 01 601 5173
Email: info@gii.ie | Web: gii.ie

### **GROUNDWATER MONITORING**

### **GALWAY PORT**

BOREHOLE	DATE	TIME	GROUNDWATER (mBGL)	Comments
WS-04	03/09/2019	16.34	1.80	
WS-09	03/09/2019	15.45	DRY	
WS-10	03/09/2019	17.15	DRY	
WS-12	03/09/2019	16.40	DRY	
WS-14	03/09/2019	18.15	DRY	
WS-16	03/09/2019	16.25	DRY	
WS-18	03/09/2019	17.31	2.60	
WS-23	03/09/2019	16.55	DRY	



(V1 August 2018)

THE PERSON NAMED IN		(VI August 2	010,					
Project Number	8979	-08-19	Sam	ple Date		19-09	-2019	
Client	М	КО	W	ell I.D.		WS	5-04	
Site Name	Galwa	ay Port	We	eather		D	ry	
Sampler I.D.	Р	M	Weather Previous 24hrs			Dry		
·		Well D	ata					
Casing Diameter (mm)	100	)mm	Total We	ell Depth (	m)	2.	04	
Standpipe Diam. (mm)	50	mm	Water Le	vel (mBT	DC)	D	ry	
Stick Up (mm)	Fli	ush	VOC Screen	in casing	(y/n)	1	V	
Standpipe Type pvc, HDPE etc.	P	VC		ata (ppm		N	IA	
		Purge I	Data					
Time Purging Start	13	.25	Sampli	ing Metho	od/Equ	ipment (T	ick)	
Timer Purging End	13	.27	Submer	sible Pun	пр			
Purge Volume (litres)		0	В	ailer			V	
Colour	N	IA	Tube wit	:h foot va	lve			
Recovery	Po	oor	Low Flo	w Pumpir	ng			
Time	Litres Purged	Ph	EC (mS)	Temp	ORP	DO (mg/l)	Odour	
2 minutes	Dry	NA	NA	NA	NA	NA	NA	
		ı	1	1	1	1	1	

#### **Additional Comments/Observations:**



(V1 August 2018)

Project Number 8979-08-19 Sample Date  Client MKO Well I.D.  Site Name Galway Port Weather  Sampler I.D. PM Weather Previous 24h  Well Data  Casing Diameter (mm) 100mm Total Well Depth (m)  Standpipe Diam. (mm) 50mm Water Level (mBTOC)  Stick Up (mm) Flush VOC Screen in casing (v)  Standpipe Type pvc, HDPE etc. PVC VOC Data (ppm)  Purge Data  Time Purging Start 16.12 Sampling Method  Timer Purging End 16.14 Submersible Pump		10.00		
Site Name  Sampler I.D.  PM  Weather Previous 24h  Well Data  Casing Diameter (mm)  Standpipe Diam. (mm)  Stick Up (mm)  Standpipe Type pvc, HDPE etc.  PVC  VOC Data (ppm)  Purge Data  Time Purging Start  Sampling Method		19-09	-2019	
Sampler I.D.  PM  Weather Previous 24h  Well Data  Casing Diameter (mm)  Standpipe Diam. (mm)  Stick Up (mm)  Standpipe Type pvc, HDPE etc.  PVC  VOC Data (ppm)  Purge Data  Time Purging Start  Mell Data  Vell Data  Vode Screen in casing (value)  Voc Screen in casing (value)  Voc Data (ppm)  Purge Data		WS	5-09	
Casing Diameter (mm)  100mm  Total Well Depth (mm)  Standpipe Diam. (mm)  Stick Up (mm)  Standpipe Type pvc, HDPE etc.  PVC  VOC Data (ppm)  Purge Data  Time Purging Start  16.12  Sampling Method		D	ry	
Casing Diameter (mm)  100mm  Total Well Depth (mm)  Standpipe Diam. (mm)  Stick Up (mm)  Standpipe Type pvc, HDPE etc.  PVC  VOC Data (ppm)  Purge Data  Time Purging Start  16.12  Sampling Method	hrs	Dry		
Standpipe Diam. (mm)  Stick Up (mm)  Standpipe Type pvc, HDPE etc.  PVC  Purge Data  Time Purging Start  50mm  Water Level (mBTOC)  Flush  VOC Screen in casing (value)  VOC Data (ppm)  Purge Data  Sampling Method				
Stick Up (mm)  Standpipe Type pvc, HDPE etc.  PVC  Purge Data  Time Purging Start  Flush  VOC Screen in casing (voc Screen in casing	1)	1.	65	
Standpipe Type pvc, HDPE etc. PVC VOC Data (ppm)  Purge Data  Time Purging Start 16.12 Sampling Method	C)	D	ry	
Standpipe Type pvc, HDPE etc. PVC VOC Data (ppm)  Purge Data  Time Purging Start 16.12 Sampling Method	y/n)	1	V	
Time Purging Start 16.12 Sampling Method		N	IA	
Timer Purging End 16.14 Submersible Pump	d/Equi	ipment (T	ick)	
	)			
Purge Volume (litres) 0 Bailer	0 Bailer		V	
Colour NA Tube with foot valve	e			
Recovery Poor Low Flow Pumping	3			
Litres Time Purged Ph EC (mS) Temp	ORP	DO (mg/l)	Odour	
2 minutes Dry NA NA NA	NA	NA	NA	

### Additional Comments/Observations:



(V1 August 2018)

THE PROPERTY OF		(VI August 2	010,				
Project Number	8979	-08-19	Sam	ple Date		19-09	-2019
Client	М	КО	W	ell I.D.		WS	5-10
Site Name	Galwa	ay Port	We	eather		D	ry
Sampler I.D.	P	M	Weather P	revious 2	4hrs	D	ry
·		Well D	ata			•	•
Casing Diameter (mm)	100	)mm	Total We	ell Depth (	m)	2.	18
Standpipe Diam. (mm)	50	mm		vel (mBT	<u> </u>	D	ry
Stick Up (mm)	Flo	ush	VOC Screen	in casing	(y/n)		N
Standpipe Type pvc, HDPE etc.		VC		ata (ppm		N	IA
		Purge I	Data				
Time Purging Start	16	.25	Sampli	ing Metho	od/Equ	ipment (1	ick)
Timer Purging End	16	5.27	Submer	sible Pun	пр		
Purge Volume (litres)		0	Bailer			V	
Colour	N	IA	Tube wit	:h foot va	lve		
Recovery	Po	oor	Low Flo	w Pumpir	ng		
Time	Litres Purged	Ph	EC (mS)	Temp	ORP	DO (mg/l)	Odour
2 minutes	Dry	NA	NA	NA	NA	NA	NA
			_1	l .	1	i .	

#### **Additional Comments/Observations:**



(V1 August 2018)

		(VI August 2	010)					
Project Number	8979	-08-19	Sam	ple Date		19-09	-2019	
Client	М	КО	W	ell I.D.		WS	5-12	
Site Name	Galwa	ay Port	We	eather		D	ry	
Sampler I.D.	Р	М	Weather P	revious 2	4hrs	s Dry		
		Well D	ata			•		
Casing Diameter (mm)	100	)mm	Total We	ell Depth (	m)	2.	10	
Standpipe Diam. (mm)	50	mm	Water Le	vel (mBT	OC)	D	ry	
Stick Up (mm)	Flu	ush	VOC Screen	in casing	; (y/n)	1	N	
Standpipe Type pvc, HDPE etc.	P'	VC	VOC D	ata (ppm	)	N	IA	
		Purge (	Data					
Time Purging Start	15	.58	Sampli	ing Metho	od/Equ	ipment (T	ick)	
Timer Purging End	16	.00	Submer	Submersible Pump				
Purge Volume (litres)	1	0 Bailer				V		
Colour	N	IA	Tube wit	:h foot va	lve			
Recovery	Po	oor	Low Flo	w Pumpir	ng			
Time	Litres Purged	Ph	EC (mS)	Temp	ORP	DO (mg/l)	Odour	
2 minutes	Dry	NA	NA	NA	NA	NA	NA	
_								

### Additional Comments/Observations:



(V1 August 2018)

THE PERSON NAMED IN		(VI August 2	.010/				
Project Number	8979	-08-19	Sam	ple Date		19-09	9-2019
Client	М	КО	W	ell I.D.		WS	S-14
Site Name	Galwa	ay Port	We	eather		D	ry
Sampler I.D.	Р	M	Weather P	revious 2	4hrs	D	ry
·		Well D	ata				
Casing Diameter (mm)	100	)mm	Total We	ell Depth (	m)	2.	30
Standpipe Diam. (mm)	50	mm	Water Le	vel (mBT	OC)	D	ry
Stick Up (mm)	Fli	ush	VOC Screen	in casing	; (y/n)	1	N
Standpipe Type pvc, HDPE etc.	P	VC		ata (ppm		N	IA
		Purge I	Data				
Time Purging Start	13	.18	Sampli	ing Metho	od/Equ	ipment (T	īck)
Timer Purging End	13	.20	Submer	sible Pum	пр		
Purge Volume (litres)		0	В	ailer			٧
Colour	N	IA.	Tube wit	:h foot va	lve		
Recovery	Po	oor	Low Flo	w Pumpir	ng		
Time	Litres Purged	Ph	EC (mS)	Temp	ORP	DO (mg/l)	Odour
2 minutes	Dry	NA	NA	NA	NA	NA	NA
		ı	1	1		1	

#### **Additional Comments/Observations:**



(V1 August 2018)

M. A. S. A.		(VI August 2	010)					
Project Number	8979-	-08-19	Sam	ple Date		19-09	9-2019	
Client	М	КО	W	ell I.D.		WS	S-16	
Site Name	Galwa	ay Port	We	eather		D	ry	
Sampler I.D.	Р	М	Weather P	revious 2	4hrs	rs Dry		
		Well D	ata					
Casing Diameter (mm)	100	)mm	Total We	ell Depth (	(m)	2.	12	
Standpipe Diam. (mm)	50	mm	Water Le	vel (mBT	OC)	D	ry	
Stick Up (mm)	Flı	ush	VOC Screen	in casing	(y/n)		N	
Standpipe Type pvc, HDPE etc.	P	VC		ata (ppm	-	N	IA	
		Purge [	Data					
Time Purging Start	13	.08	Sampli	ing Metho	od/Equ	ipment (1	ick)	
Timer Purging End	13	.10	Submer	Submersible Pump				
Purge Volume (litres)		0		Bailer			٧	
Colour	N	IA	Tube wit	:h foot va	lve			
Recovery	Pc	oor	Low Flo	w Pumpir	ng			
Time	Litres Purged	Ph	EC (mS)	Temp	ORP	DO (mg/l)	Odour	
2 minutes	Dry	NA	NA	NA	NA	NA	NA	
				1	<u> </u>			

### Additional Comments/Observations:



(V1 August 2018)

		1 10:11	/				
Project Number	8979	-08-19	Sam	ple Date		19-09	-2019
Client	М	КО	We	ell I.D.		WS	5-18
Site Name	Galwa	ay Port	We	eather		D	ry
Sampler I.D.	Р	M	Weather P	revious 2	4hrs	D	ry
		Well D	ata				
Casing Diameter (mm)	100	)mm	Total We	ell Depth (	(m)	2.	72
Standpipe Diam. (mm)	50	mm	Water Le	vel (mBT	OC)	2.	63
Stick Up (mm)	Flu	ush	VOC Screen	in casing	; (y/n)	ı	V
Standpipe Type pvc, HDPE etc.	P	VC	VOC D	ata (ppm	)	Ν	IA
		Purge D	ata				
Time Purging Start	13	.44	Sampli	ing Metho	od/Equ	ipment (T	ick)
Timer Purging End	13	.46	Submer	ubmersible Pump			
Purge Volume (litres)	То	To Dry		Bailer			V
Colour	Dark	Brown	Tube wit	h foot va	lve		
Recovery	Po	oor	Low Flo	w Pumpir	ng		
Time	Litres Purged	Ph	EC (mS)	Temp	ORP	DO (mg/l)	Odour
2 minutes	To Dry	7.32	13.32	18.6	NA	NA	None
					•		

### Additional Comments/Observations:



(V1 August 2018)

	ALT THE AREA OF		(VI August 2	.010)					
Site Name Galway Port Weather Dry  Sampler I.D. PM Weather Previous 24hrs Dry  Well Data  Casing Diameter (mm) 100mm Total Well Depth (m) 2.42  Standpipe Diam. (mm) 50mm Water Level (mBTOC) Dry  Stick Up (mm) Flush VOC Screen in casing (y/n) N  Standpipe Type pvc, HDPE etc. PVC VOC Data (ppm) NA  Purge Data  Time Purging Start 14.28 Sampling Method/Equipment (Tick)  Timer Purging End 14.30 Submersible Pump  Purge Volume (litres) Dry Bailer V  Colour NA Tube with foot valve  Recovery Poor Low Flow Pumping  Time Purged Ph EC (mS) Temp ORP (mg/l) O	Project Number	8979	-08-19	Sam	ple Date		19-09	-2019	
Sampler I.D. PM Weather Previous 24hrs Dry  Well Data  Casing Diameter (mm) 100mm Total Well Depth (m) 2.42  Standpipe Diam. (mm) 50mm Water Level (mBTOC) Dry  Stick Up (mm) Flush VOC Screen in casing (y/n) N  Standpipe Type pvc, HDPE etc. PVC VOC Data (ppm) NA  Purge Data  Time Purging Start 14.28 Sampling Method/Equipment (Tick)  Timer Purging End 14.30 Submersible Pump  Purge Volume (litres) Dry Bailer V  Colour NA Tube with foot valve  Recovery Poor Low Flow Pumping  Time Purged Ph EC (mS) Temp ORP (mg/l) O	Client	М	КО	W	ell I.D.		WS	5-23	
Well Data         Casing Diameter (mm)       100mm       Total Well Depth (m)       2.42         Standpipe Diam. (mm)       50mm       Water Level (mBTOC)       Dry         Stick Up (mm)       Flush       VOC Screen in casing (y/n)       N         Standpipe Type pvc, HDPE etc.       PVC       VOC Data (ppm)       NA         Purge Data         Time Purging Start       14.28       Sampling Method/Equipment (Tick)         Timer Purging End       14.30       Submersible Pump         Purge Volume (litres)       Dry       Bailer       V         Colour       NA       Tube with foot valve         Recovery       Poor       Low Flow Pumping         Litres       Purged       Ph       EC (mS)       Temp       ORP       (mg/l)       O	Site Name	Galwa	ay Port	We	eather		D	ry	
Casing Diameter (mm) 100mm Total Well Depth (m) 2.42  Standpipe Diam. (mm) 50mm Water Level (mBTOC) Dry  Stick Up (mm) Flush VOC Screen in casing (y/n) N  Standpipe Type pvc, HDPE etc. PVC VOC Data (ppm) NA  Purge Data  Time Purging Start 14.28 Sampling Method/Equipment (Tick)  Timer Purging End 14.30 Submersible Pump  Purge Volume (litres) Dry Bailer V  Colour NA Tube with foot valve  Recovery Poor Low Flow Pumping  Litres Purged Ph EC (mS) Temp ORP (mg/l) O	Sampler I.D.	P	М	Weather P	revious 2	4hrs	Dry		
Standpipe Diam. (mm)  Stick Up (mm)  Standpipe Type pvc, HDPE etc.  PVC  Purge Data  Time Purging Start  14.28  Sampling Method/Equipment (Tick)  Timer Purging End  14.30  Submersible Pump  Purge Volume (litres)  Dry  Bailer  V  Colour  NA  Tube with foot valve  Recovery  Poor  Low Flow Pumping  Litres Purged  Ph  EC (mS)  Temp  ORP  ORP  Indicates  Dry  Dry  Bry  DO  (mg/l)  Orr  ORP			Well D	ata			•		
Stick Up (mm)  Standpipe Type pvc, HDPE etc.  PVC  VOC Data (ppm)  NA  Purge Data  Time Purging Start  14.28  Sampling Method/Equipment (Tick)  Timer Purging End  14.30  Submersible Pump  Purge Volume (litres)  Dry  Bailer  V  Colour  NA  Tube with foot valve  Recovery  Poor  Low Flow Pumping  Litres Purged  Ph  EC (mS)  Temp  ORP  (mg/l)  O	Casing Diameter (mm)	100	)mm	Total We	ell Depth (	m)	2.	42	
Standpipe Type pvc, HDPE etc.  Purge Data  Time Purging Start  14.28  Sampling Method/Equipment (Tick)  Timer Purging End  14.30  Submersible Pump  Purge Volume (litres)  Dry  Bailer  V  Colour  NA  Tube with foot valve  Recovery  Poor  Low Flow Pumping  Litres Purged  Ph  EC (mS)  Temp  ORP  ORP  (mg/l)  O	Standpipe Diam. (mm)	50	mm	Water Le	vel (mBT	OC)	D	ry	
Standpipe Type pvc, HDPE etc.  Purge Data  Time Purging Start  14.28  Sampling Method/Equipment (Tick)  Timer Purging End  14.30  Submersible Pump  Purge Volume (litres)  Dry  Bailer  V  Colour  NA  Tube with foot valve  Recovery  Poor  Low Flow Pumping  Litres Purged  Ph  EC (mS)  Temp  ORP  ORP  (mg/l)  O	Stick Up (mm)	Fli	ush	VOC Screen	in casing	; (y/n)	1	N	
Time Purging Start  14.28  Sampling Method/Equipment (Tick)  Timer Purging End  14.30  Submersible Pump  Purge Volume (litres)  Dry  Bailer  V  Colour  NA  Tube with foot valve  Recovery  Poor  Low Flow Pumping  Litres  Purged  Ph  EC (mS)  Temp  ORP  (mg/l)  O		P'	VC				N	IA	
Timer Purging End  14.30  Submersible Pump  Purge Volume (litres)  Dry  Bailer  V  Colour  NA  Tube with foot valve  Recovery  Poor  Low Flow Pumping  Litres  Purged  Ph  EC (mS)  Temp  ORP  (mg/l)  O			Purge I	Data					
Purge Volume (litres)  Colour  NA  Tube with foot valve  Recovery  Poor  Litres Purged  Ph  EC (mS)  Temp  ORP  (mg/l)  O	Time Purging Start	14	.28	Sampli	ing Metho	od/Equ	ipment (T	ick)	
Colour NA Tube with foot valve  Recovery Poor Low Flow Pumping  Litres DO  Purged Ph EC (mS) Temp ORP (mg/l) O	Timer Purging End	14	.30	Submer	Submersible Pump				
Recovery Poor Low Flow Pumping  Litres DO Purged Ph EC (mS) Temp ORP (mg/l) O	Purge Volume (litres)	D	Dry		Bailer			٧	
Litres DO Time Purged Ph EC (mS) Temp ORP (mg/l) O	Colour	N	IA	Tube wit	:h foot va	lve			
Time Purged Ph EC (mS) Temp ORP (mg/l) O	Recovery	Po	oor	Low Flo	w Pumpir	ng			
2 minutes Dry NA NA NA NA NA	Time		Ph	EC (mS)	Temp	ORP		Odour	
	2 minutes	Dry	NA	NA	NA	NA	NA	NA	

### Additional Comments/Observations:



(V1 August 2018)

m. n = met nex		(VI August Zi	1101					
Project Number	8979	-08-19	Samı	ole Date		19-09	-2019	
Client	М	КО	We	ell I.D.		WS	5-28	
Site Name	Galwa	ay Port	We	eather		D	ry	
Sampler I.D.	Р	М	Weather P	revious 2	4hrs	D	ry	
·		Well Da	ata					
Casing Diameter (mm)	100	)mm	Total We	ll Depth (	m)	6.	85	
Standpipe Diam. (mm)	50	mm	Water Le	vel (mBT0	OC)	4.	4.58	
Stick Up (mm)	Fli	ush	VOC Screen	in casing	(y/n)	1	N	
Standpipe Type pvc, HDPE etc.	Р	VC		VOC Data (ppm)				
		Purge D	ata					
Time Purging Start	14	.20	Sampli	ng Method/Equipment (Tick)				
Timer Purging End	14	.34	Submersible Pump					
Purge Volume (litres)	21 l	itres	В	ailer		,	V	
Colour	Light	Brown	Tube wit	h foot val	lve			
Recovery	Go	ood	Low Flo	w Pumpir	ng			
Time	Litres Purged	Ph	EC (mS)	Temp	ORP	DO (mg/l)	Odour	
14 minutes	21	7.61	11.45	19.1	NA	NA	None	
		•	•	•	•	•	•	



(V1 August 2018)

THE RESIDENCE IS		(VI August 20	,10,				
Project Number	8979	-08-19	Samp	ole Date		19-09	9-2019
Client	М	IKO	We	ell I.D.		WS	S-29
Site Name	Galwa	ay Port	We	eather		D	ry
Sampler I.D.	P	PM	Weather P	revious 2	4hrs	D	ry
·		Well Da	ata				•
Casing Diameter (mm)	100	)mm	Total We	ll Depth (	m)	5.	.14
Standpipe Diam. (mm)		mm	Water Le		<u> </u>		.43
Stick Up (mm)		ush	VOC Screen in casing (y/n) N				N
Standpipe Type pvc, HDPE etc.		VC	VOC D		NA		
		Purge D	ata				
Time Purging Start	15	5.23	Sampling Method/Equipment (Tick)				
Timer Purging End	15	5.42	Submersible Pump				
Purge Volume (litres)	14 l	_itres	В	ailer			٧
Colour	ВІ	ack	Tube wit	h foot va	lve		
Recovery	Go	ood	Low Flo	w Pumpir	ng		
Time	Litres Purged	Ph	EC (mS)	Temp	ORP	DO (mg/l)	Odour
19 minutes	14	8.21	15.65	17.4	NA	NA	Organic



(V1 August 2018)

		(VI / Nagast I	.0101					
Project Number	8979	-08-19	Sam	ple Date		04-10	-2019	
Client	М	КО	W	ell I.D.		WS	5-04	
Site Name	Galwa	ay Port	We	Weather		W	/et	
Sampler I.D.	P	M	Weather P	revious 2	4hrs	W	/et	
·		Well D	)ata			I		
Casing Diameter (mm)	100	)mm		ell Depth (	m)	2.	03	
Standpipe Diam. (mm)	50	mm		vel (mBT		2.00		
Stick Up (mm)		ush	VOC Screen	·			N	
Standpipe Type pvc, HDPE etc.		VC		ata (ppm		NA		
		Purge l	Data					
Time Purging Start	14	.21	Sampli	Sampling Method/Equipment (Tick)				
Timer Purging End	14	.22	Submer	Submersible Pump				
Purge Volume (litres)	То	Dry	В	ailer			V	
Colour	Light	Brown	Tube wit	h foot va	lve			
Recovery	Po	oor	Low Flo	w Pumpir	ng			
Time	Litres Purged	Ph	EC (mS)	Temp	ORP	DO (mg/l)	Odour	
1 minute	Dry	NA	NA	NA	NA	NA	None	
		l		_1	<u> </u>	I	1	

### Additional Comments/Observations:



(V1 August 2018)

		(VI / lagast I	.0101					
Project Number	8979	-08-19	Sam	ple Date		04-10	)-2019	
Client	М	КО	W	Well I.D. WS-09				
Site Name	Galwa	ay Port	We	eather		W	/et	
Sampler I.D.	Р	M	Weather P	revious 2	4hrs	W	/et	
·		Well D	ata			I		
Casing Diameter (mm)	100	)mm	Total We	ell Depth (	m)	1.	65	
Standpipe Diam. (mm)	50	mm		vel (mBT	-	D	Dry	
Stick Up (mm)	Flr	ush	VOC Screen				N	
Standpipe Type pvc, HDPE etc.	P	VC	VOC D	ata (ppm	)	NA		
		Purge l	Data					
Time Purging Start	N	NA	Sampli	mpling Method/Equipment (Tick)				
Timer Purging End	N	NA .	Submer	ubmersible Pump				
Purge Volume (litres)	N	۱A	В	ailer			٧	
Colour	N	۱A	Tube wit	:h foot va	lve			
Recovery	Po	oor	Low Flo	w Pumpir	ng			
Time	Litres Purged	Ph	EC (mS)	Temp	ORP	DO (mg/l)	Odour	
NA	Dry	NA	NA	NA	NA	NA	NA	
•								
		1		1				

### Additional Comments/Observations:



(V1 August 2018)

	-	(VI August Z	010)				
Project Number	8979	-08-19	Samı	ple Date		04-10-2019	
Client	М	КО	We	ell I.D.		WS	5-10
Site Name	Galwa	ay Port	We	eather		W	et
Sampler I.D.	Р	М	Weather P	revious 2	4hrs	W	et
		Well D	ata				
Casing Diameter (mm)	100	)mm	Total We	ell Depth (	(m)	2.	15
Standpipe Diam. (mm)	50	mm	Water Le	vel (mBT0	OC)	Dry	
Stick Up (mm)	Fli	ush	VOC Screen	in casing	g (y/n)	N	
Standpipe Type pvc, HDPE etc.	P	VC	VOC Data (ppm)			NA	
		Purge D	ata				
Time Purging Start	N	IA	Sampling Method/Equipment (Tick)				
Timer Purging End	N	IA	Submer	Submersible Pump			
Purge Volume (litres)		0	В	ailer		٧	
Colour	N	IA	Tube wit	h foot va	lve		
Recovery	Po	oor	Low Flo	w Pumpir	ng		
Time	Litres Purged	Ph	EC (mS)	Temp	ORP	DO (mg/l)	Odour
NA	Dry	NA	NA	NA	NA	NA	NA

### Additional Comments/Observations:



(V1 August 2018)

		(VI / lugust I	.010,					
Project Number	8979	-08-19	Sam	ple Date		04-10	)-2019	
Client	М	КО	W	Well I.D. WS-12				
Site Name	Galwa	ay Port	We	eather		W	/et	
Sampler I.D.	Р	M	Weather P	revious 2	4hrs	W	/et	
·		Well D	Data			•		
Casing Diameter (mm)	100	)mm	Total We	ell Depth (	m)	2.	10	
Standpipe Diam. (mm)	50	mm		vel (mBT	-	D	ry	
Stick Up (mm)	Fl	ush	VOC Screen				N.	
Standpipe Type pvc, HDPE etc.		VC		ata (ppm	NA			
		Purge	Data					
Time Purging Start	N	IA.	Sampli	ng Method/Equipment (Tick)				
Timer Purging End	١	IA	Submer	ubmersible Pump				
Purge Volume (litres)	N	IA.	В	ailer			٧	
Colour	N	IA.	Tube wit	:h foot va	lve			
Recovery	Po	oor	Low Flo	w Pumpir	ng			
Time	Litres Purged	Ph	EC (mS)	Temp	ORP	DO (mg/l)	Odour	
NA	Dry	NA	NA	NA	NA	NA	NA	
	<u> </u>	I	L		<u> </u>	l	<u> </u>	

### Additional Comments/Observations:



(V1 August 2018)

		(VI / lugust I	.010,					
Project Number	8979	-08-19	Sam	ple Date		04-10	)-2019	
Client	М	КО	W	Well I.D. WS-14				
Site Name	Galwa	ay Port	We	eather		W	/et	
Sampler I.D.	Р	M	Weather P	revious 2	4hrs	W	/et	
·		Well D	Data			•		
Casing Diameter (mm)	100	)mm	Total We	ell Depth (	m)	2.	23	
Standpipe Diam. (mm)	50	mm		vel (mBT	-	D	ry	
Stick Up (mm)	Flr	ush	VOC Screen				N	
Standpipe Type pvc, HDPE etc.	P	VC		ata (ppm		NA		
		Purge	Data					
Time Purging Start	N	IA.	Sampli	mpling Method/Equipment (Tick)				
Timer Purging End	N	IA	Submer	ubmersible Pump				
Purge Volume (litres)	N	IA.	В	ailer			٧	
Colour	N	IA.	Tube wit	:h foot va	lve			
Recovery	Po	oor	Low Flo	w Pumpir	ng			
Time	Litres Purged	Ph	EC (mS)	Temp	ORP	DO (mg/l)	Odour	
NA	Dry	NA	NA	NA	NA	NA	NA	
	<u> </u>	I	L		<u> </u>	1	<u> </u>	

### Additional Comments/Observations:



(V1 August 2018)

		(VI / tagast I	.010/					
Project Number	8979	-08-19	Sam	ple Date		04-10	)-2019	
Client	М	КО	W	Well I.D. WS-16				
Site Name	Galwa	ay Port	We	Weather			/et	
Sampler I.D.	Р	M	Weather P	revious 2	4hrs	W	/et	
·		Well D	ata					
Casing Diameter (mm)	100	)mm	Total We	ell Depth (	(m)	2.	06	
Standpipe Diam. (mm)	50	mm	Water Le	vel (mBT	OC)	D	Dry	
Stick Up (mm)	Flo	ush	VOC Screen				N	
Standpipe Type pvc, HDPE etc.	P	VC	VOC D	ata (ppm	)	NA		
		Purge	Data					
Time Purging Start	N	NA .	Sampli	Sampling Method/Equipment (Tick)				
Timer Purging End	N	NA .	Submer	Submersible Pump				
Purge Volume (litres)	N	NA	В	ailer			V	
Colour	N	NA	Tube wit	:h foot va	lve			
Recovery	Po	oor	Low Flo	w Pumpir	ng			
Time	Litres Purged	Ph	EC (mS)	Temp	ORP	DO (mg/l)	Odour	
NA	Dry	NA	NA	NA	NA	NA	NA	
		•						

### Additional Comments/Observations:



(V1 August 2018)

		(TI / tagast L	010,					
Project Number	8979	-08-19	Sam	ple Date		04-10	-2019	
Client	М	КО	We	ell I.D.		WS	5-18	
Site Name	Galwa	ay Port	We	eather		W	/et	
Sampler I.D.	P	M	Weather P	revious 2	4hrs	W	/et	
·		Well D	ata			Į.		
Casing Diameter (mm)	100	)mm		ell Depth (	(m)	2.	70	
Standpipe Diam. (mm)	50	mm	Water Le	•	-	2.62		
Stick Up (mm)		ush	VOC Screen in casing (y/n)				N	
Standpipe Type pvc, HDPE etc.		VC		ata (ppm		NA		
		Purge [	Data					
Time Purging Start	11	57	Sampli	ampling Method/Equipment (Tick)				
Timer Purging End	12	2.00	Submersible Pump					
Purge Volume (litres)	1 litre	to Dry	В	ailer			V	
Colour	ВІ	ack	Tube wit	h foot va	lve			
Recovery	Po	oor	Low Flo	w Pumpir	ng			
Time	Litres Purged	Ph	EC (mS)	Temp	ORP	DO (mg/l)	Odour	
3 minutes	To Dry	7.25	12.32	13.6	NA	NA	None	
		l .	_1	1	1	1	1	

### Additional Comments/Observations:



(V1 August 2018)

		(VI / tagast I	.010,					
Project Number	8979	-08-19	Sam	ple Date		04-10	)-2019	
Client	М	КО	W	Well I.D. WS-23				
Site Name	Galwa	ay Port	We	eather		W	/et	
Sampler I.D.	Р	M	Weather P	revious 2	4hrs	W	/et	
·		Well [	Data			•		
Casing Diameter (mm)	100	)mm	Total We	ell Depth (	m)	2.	40	
Standpipe Diam. (mm)	50	mm	Water Le	vel (mBT	OC)	D	Dry	
Stick Up (mm)	Flo	ush	VOC Screen	in casing	; (y/n)	1	N	
Standpipe Type pvc, HDPE etc.	P	VC	VOC D	ata (ppm	)	NA		
		Purge	Data					
Time Purging Start	N	IA.	Sampli	npling Method/Equipment (Tick)				
Timer Purging End	N	IA.	Submer	Submersible Pump				
Purge Volume (litres)	D	ry	В	ailer		,	V	
Colour	N	IA.	Tube wit	:h foot va	lve			
Recovery	Po	oor	Low Flo	w Pumpir	ng			
Time	Litres Purged	Ph	EC (mS)	Temp	ORP	DO (mg/l)	Odour	
NA	Dry	NA	NA	NA	NA	NA	NA	
•								
	·			1		1	·	

### Additional Comments/Observations:



(V1 August 2018)

THE MAN TO		(VI August 20	)18)					
Project Number	8979	-08-19	Samp	ole Date	e 04-10-2019			
Client	М	КО	We	ell I.D.		WS	5-28	
Site Name	Galwa	ay Port	We	eather		W	/et	
Sampler I.D.	Р	М	Weather P	revious 2	4hrs	W	/et	
		Well Da	ata					
Casing Diameter (mm)	100	)mm	Total We	ll Depth (	m)	6.	81	
Standpipe Diam. (mm)	50	mm	Water Le	vel (mBT0	DC)	4.	37	
Stick Up (mm)	Flu	ush	VOC Screen	N				
Standpipe Type pvc, HDPE etc.	P	VC	VOC D	ata (ppm)	)	NA		
		Purge D	ata					
Time Purging Start	13	.06	Sampli	Sampling Method/Equipment (Tick)				
Timer Purging End	13	.30	Submersible Pump					
Purge Volume (litres)	26 Լ	itres	В	ailer		,	V	
Colour	Clear to li	ght brown	Tube wit	h foot va	lve			
Recovery	Go	ood	Low Flor	w Pumpir	ng			
Time	Litres Purged	Ph	EC (mS)	Temp	ORP	DO (mg/l)	Odour	
24 minutes	26	7.46	11.25	15.1	NA	NA	None	
Additional Community /O	h	·	•	•				



(V1 August 2018)

		(VI August Zu	10)						
Project Number	8979	-08-19	Samp	ole Date	Pate 04-10-2019				
Client	М	КО	We	ell I.D.		WS	S-29		
Site Name	Galwa	ay Port	We	ather		W	/et		
Sampler I.D.	Р	М	Weather P	revious 2	4hrs	W	/et		
·		Well Da	nta						
Casing Diameter (mm)	100	)mm	Total We	ll Depth (	m)	5.	11		
Standpipe Diam. (mm)	50	mm	Water Le	vel (mBT0	DC)	3.	61		
Stick Up (mm)	Fli	ush	VOC Screen	in casing	(y/n)		N		
Standpipe Type pvc, HDPE etc.	Р	VC	VOC Da	N	NA				
		Purge D	ata						
Time Purging Start	12	.05	Sampli	Sampling Method/Equipment (Tick)					
Timer Purging End	12	.27	Submer						
Purge Volume (litres)	21 l	itres	В	ailer		,	٧		
Colour	Clear t	o black	Tube wit	h foot val	ve				
Recovery	Go	ood	Low Flov	w Pumpir	ng				
Time	Litres Purged	Ph	EC (mS)	Temp	ORP	DO (mg/l)	Odour		
19 minutes	21	8.11	15.25	14.4	NA	NA	Organic		
		I	ı	1			1		





# APPENDIX 5

LABORATORY RESULTS



Unit 3 Deeside Point

Zone 3

Deeside Industrial Park

Deeside CH5 2UA P: +44 (0) 1244 833780

F: +44 (0) 1244 833781

W: www.element.com

Ground Investigations Ireland Catherinestown House Hazelhatch Road Newcastle Co. Dublin Ireland





Attention: Barry Sexton

Date: 20th September, 2019

**Your reference**: 8979-08-19

Our reference : Test Report 19/14295 Batch 1

**Location :** Galway Docklands/Port

Date samples received : 5th September, 2019

Status: Final report

Issue:

Thirty five samples were received for analysis on 5th September, 2019 of which thirty five were scheduled for analysis. Please find attached our Test Report which should be read with notes at the end of the report and should include all sections if reproduced. Interpretations and opinions are outside the scope of any accreditation, and all results relate only to samples supplied.

All analysis is carried out on as received samples and reported on a dry weight basis unless stated otherwise. Results are not surrogate corrected.

**Authorised By:** 

Phil Sommerton BSc

Senior Project Manager

Please include all sections of this report if it is reproduced

Client Name: Ground Investigations Ireland

**Reference:** 8979-08-19

Location: Galway Docklands/Port

Contact: Barry Sexton EMT Job No: 19/14295

Report : Solid

EMT Job No:	19/14295												
EMT Sample No.	1-3	4-6	7-9	10-12	13-15	16-18	19-21	22-24	25-27	28-30			
Sample ID	WS-01	WS-02	WS-03	WS-04	WS-04	WS-04	WS-05	WS-05	WS-07	WS-09			
Depth	0.00-0.50	0.00-0.50	0.00-0.54	0.00-1.00	1.00-2.00	2.00-2.20	0.00-1.00	1.00-1.70	0.00-0.70	0.00-1.00		e attached n ations and a	
COC No / misc											abblevi	ations and a	DIOTIVITIS
Containers	VJT												
Sample Date	02/09/2019	02/09/2019	02/09/2019	02/09/2019	02/09/2019	02/09/2019	02/09/2019	02/09/2019	30/08/2019	30/08/2019			
Sample Type	Soil												
Batch Number	1	1	1	1	1	1	1	1	1	1	1.00/1.00	Units	Method
Date of Receipt	05/09/2019	05/09/2019	05/09/2019	05/09/2019	05/09/2019	05/09/2019	05/09/2019	05/09/2019	05/09/2019	05/09/2019	LOD/LOR	Units	No.
Antimony	1	<1	<1	<1	<1	<1	<1	<1	<1	2	<1	mg/kg	TM30/PM15
Arsenic #	3.5	3.4	3.8	2.1	2.0	2.1	2.6	3.0	2.8	16.5	<0.5	mg/kg	TM30/PM15
Barium #	187	433	324	28	21	22	36	35	28	444	<1	mg/kg	TM30/PM15
Cadmium#	0.8	0.4	0.5	0.6	0.3	0.3	0.4	0.5	0.4	0.9	<0.1	mg/kg	TM30/PM15
Chromium #	22.3	31.7	32.3	38.4	60.4	60.2	82.7	35.5	25.8	57.8	<0.5	mg/kg	TM30/PM15
Copper#	21	14	15	11	11	9	25	13	12	88	<1	mg/kg	TM30/PM15
Lead#	47	38	31	33	9	9	53	16	35	300	<5	mg/kg	TM30/PM15
Mercury #	<0.1	<0.1	<0.1	<0.1	<0.1	<0.1	<0.1	<0.1	<0.1	0.5	<0.1	mg/kg	TM30/PM15
Molybdenum #	1.6	2.6	2.2	2.1	3.2	3.5	4.5	1.7	2.2	3.8	<0.1	mg/kg	TM30/PM15
Nickel #	7.9	10.8	10.6	8.4	9.2	6.9	10.9	11.0	8.1	17.1	<0.7	mg/kg	TM30/PM15
Selenium# Zinc#	<1 123	<1	<1 55	<1 37	<1 24	<1 39	<1 62	<1 28	<1 48	<1 352	<1 <5	mg/kg	TM30/PM15 TM30/PM15
Antimony	-	41	-	-	-	-	-	-	-	-	<1	mg/kg mg/kg	TM30/PM62
Arsenic	_	-	-	- -	-	-	-	-	-	-	<0.5	mg/kg	TM30/PM62
Barium	_	-	-	_	-	_	_	_	-	_	<1	mg/kg	TM30/PM62
Cadmium	-	-	-	-	_	-	_	_	_	_	<0.1	mg/kg	TM30/PM62
Chromium	-	-	-	-	-	-	-	-	-	-	<0.5	mg/kg	TM30/PM62
Copper	-	-	-	-	-	-	-	-	-	-	<1	mg/kg	TM30/PM62
Lead	-	-	-	-	-	-	-	-	-	-	<5	mg/kg	TM30/PM62
Mercury	-	-	-	-	-	-	-	-	-	-	<0.1	mg/kg	TM30/PM62
Molybdenum	-	-	-	-	-	-	-	-	-	-	<0.1	mg/kg	TM30/PM62
Nickel	-	-	-	-	-	-	-	-	-	-	<0.7	mg/kg	TM30/PM62
Selenium	-	-	-	-	-	-	-	-	-	-	<1	mg/kg	TM30/PM62
Zinc	-	-	-	-	-	-	-	-	-	-	<5	mg/kg	TM30/PM62

Client Name: Ground Investigations Ireland

**Reference:** 8979-08-19

Location: Galway Docklands/Port

Contact: Barry Sexton EMT Job No: 19/14295

Report : Solid

EMT Job No:	19/14295												
EMT Sample No.	1-3	4-6	7-9	10-12	13-15	16-18	19-21	22-24	25-27	28-30			
Sample ID	WS-01	WS-02	WS-03	WS-04	WS-04	WS-04	WS-05	WS-05	WS-07	WS-09			
Depth	0.00-0.50	0.00-0.50	0.00-0.54	0.00-1.00	1.00-2.00	2.00-2.20	0.00-1.00	1.00-1.70	0.00-0.70	0.00-1.00		ee attached r	
COC No / misc											abblevi	ations and a	Cionyma
Containers	VJT	VJT	VJT	VJT	VJT	VJT	VJT	VJT	VJT	VJT			
Sample Date	02/09/2019	02/09/2019	02/09/2019	02/09/2019	02/09/2019	02/09/2019	02/09/2019	02/09/2019	30/08/2019	30/08/2019			
Sample Type	Soil	Soil	Soil	Soil	Soil	Soil	Soil	Soil	Soil	Soil			
Batch Number	1	1	1	1	1	1	1	1	1	1			Method
Date of Receipt	05/09/2019	05/09/2019	05/09/2019	05/09/2019	05/09/2019	05/09/2019	05/09/2019	05/09/2019	05/09/2019	05/09/2019	LOD/LOR	Units	No.
PAH MS													
Naphthalene #	0.04	<0.04	<0.04	0.08	<0.04	<0.04	<0.04	<0.04	<0.04	0.46	<0.04	mg/kg	TM4/PM8
Acenaphthylene	<0.03	<0.03	<0.03	0.03	<0.03	<0.03	<0.03	<0.03	<0.03	0.91	<0.03	mg/kg	TM4/PM8
Acenaphthene #	<0.05	<0.05	<0.05	<0.05	<0.05	<0.05	<0.05	<0.05	<0.05	0.12	<0.05	mg/kg	TM4/PM8
Fluorene #	<0.04	<0.04	<0.04	<0.04	<0.04	<0.04	<0.04	<0.04	<0.04	0.31	<0.04	mg/kg	TM4/PM8
Phenanthrene #	0.07	<0.03	0.05	0.15	<0.03	<0.03	0.07	<0.03	0.04	3.59	<0.03	mg/kg	TM4/PM8
Anthracene #	<0.04	<0.04	<0.04	<0.04	<0.04	<0.04	<0.04	<0.04	<0.04	1.58	<0.04	mg/kg	TM4/PM8
Fluoranthene#	0.11	0.04	0.09	0.27	<0.03	<0.03	0.13	<0.03	0.06	10.51	<0.03	mg/kg	TM4/PM8
Pyrene # Benzo(a)anthracene #	0.11	0.03 <0.06	0.09	0.26 0.19	<0.03 <0.06	<0.03	0.11	<0.03 <0.06	0.05 <0.06	9.12 6.66	<0.03 <0.06	mg/kg mg/kg	TM4/PM8 TM4/PM8
Chrysene #	0.06	<0.00	0.06	0.19	<0.00	<0.00	0.12	<0.00	<0.00	5.98	<0.00	mg/kg	TM4/PM8
Benzo(bk)fluoranthene #	0.11	<0.07	0.17	0.36	<0.07	<0.07	0.18	<0.07	<0.07	11.76	<0.07	mg/kg	TM4/PM8
Benzo(a)pyrene #	0.05	<0.04	0.09	0.17	<0.04	<0.04	0.09	<0.04	<0.04	6.32	<0.04	mg/kg	TM4/PM8
Indeno(123cd)pyrene	<0.04	<0.04	0.05	0.11	<0.04	<0.04	0.05	<0.04	<0.04	3.97	<0.04	mg/kg	TM4/PM8
Dibenzo(ah)anthracene #	<0.04	<0.04	<0.04	<0.04	<0.04	<0.04	<0.04	<0.04	<0.04	0.86	<0.04	mg/kg	TM4/PM8
Benzo(ghi)perylene #	<0.04	<0.04	0.07	0.13	<0.04	<0.04	0.06	<0.04	<0.04	3.93	<0.04	mg/kg	TM4/PM8
Coronene	<0.04	<0.04	<0.04	<0.04	<0.04	<0.04	<0.04	<0.04	<0.04	0.87	<0.04	mg/kg	TM4/PM8
PAH 6 Total #	0.27	<0.22	0.47	1.04	<0.22	<0.22	0.51	<0.22	<0.22	36.49	<0.22	mg/kg	TM4/PM8
PAH 17 Total	0.64	<0.64	0.77	1.94	<0.64	<0.64	0.92	<0.64	<0.64	66.95	<0.64	mg/kg	TM4/PM8
Benzo(b)fluoranthene	0.08	<0.05	0.12	0.26	<0.05	<0.05	0.13	<0.05	<0.05	8.47	<0.05	mg/kg	TM4/PM8
Benzo(k)fluoranthene	0.03	<0.02	0.05	0.10	<0.02	<0.02	0.05	<0.02	<0.02	3.29	<0.02	mg/kg	TM4/PM8
Benzo(j)fluoranthene	<1 102	<1 98	<1 94	<1 100	<1 85	<1 88	<1 96	<1 72	<1 96	94	<1 <0	mg/kg %	TM4/PM8 TM4/PM8
PAH Surrogate % Recovery	102	90	94	100	00	00	96	12	90	94	<0	70	TIVI4/PIVIO
Mineral Oil (C10-C40)	150	<30	<30	<30	<30	<30	<30	<30	<30	<30	<30	mg/kg	TM5/PM8/PM16
TPH CWG													
Aliphatics													
>C5-C6#	<0.1 <sup>sv</sup>	<0.1 <sup>sv</sup>	<0.1 <sup>sv</sup>	<0.1	<0.1	<0.1	<0.1 <sup>sv</sup>	<0.1	<0.1	<0.1	<0.1	mg/kg	TM36/PM12
>C6-C8#	<0.1 <sup>SV</sup>	<0.1 <sup>sv</sup>	<0.1 <sup>SV</sup>	<0.1	<0.1	<0.1	<0.1 <sup>sv</sup>	<0.1	<0.1	<0.1	<0.1	mg/kg	TM36/PM12
>C8-C10	<0.1 sv	<0.1 <sup>sv</sup>	<0.1 sv	<0.1	<0.1	<0.1	<0.1 sv	<0.1	<0.1	<0.1	<0.1	mg/kg	TM36/PM12
>C10-C12#	<0.2	<0.2	<0.2	<0.2	<0.2	<0.2	<0.2	<0.2	<0.2	<0.2	<0.2	mg/kg	TM5/PM8/PM16
>C12-C16#	<4	<4	<4	<4	<4	<4	<4	<4	<4	<4	<4	mg/kg	TM5/PM8/PM16
>C16-C21#	<7	<7	<7	<7	<7	<7	<7	<7	<7	<7	<7	mg/kg	TM5/PM8/PM16
>C21-C35#	85 65	<7	<7	<7 <7	<7	<7	11 <7	<7	12	<7 <7	<7 <7	mg/kg	TM5/PM8/PM16 TM5/PM8/PM16
>C35-C40 Total aliphatics C5-40	65 150	<7 <26	<7 <26		<7 <26	<7 <26	<26	<7 <26	<7 <26		<7 <26	mg/kg mg/kg	TM5/PM8/PM16 TM5/TM38/PM8/PM12/PM16
>C6-C10	<0.1 <b>SV</b>	<0.1 <b>sv</b>	<0.1 <b>sv</b>	<0.1	<0.1	<0.1	<0.1 <sup>SV</sup>	<0.1	<0.1	<0.1	<0.1	mg/kg	TM36/PM12
>C10-C25	<10	<10	<10	<10	<10	<10	<10	<10	<10	<10	<10	mg/kg	TM5/PM8/PM16
>C25-C35	86	<10	<10	<10	<10	<10	11	<10	12	<10	<10	mg/kg	TM5/PM8/PM16
												J U	

Client Name: Ground Investigations Ireland

**Reference:** 8979-08-19

Location: Galway Docklands/Port

Contact: Barry Sexton EMT Job No: 19/14295

Report : Solid

EMT Job No:	19/14295										_		
EMT Sample No.	1-3	4-6	7-9	10-12	13-15	16-18	19-21	22-24	25-27	28-30			
Sample ID	WS-01	WS-02	WS-03	WS-04	WS-04	WS-04	WS-05	WS-05	WS-07	WS-09			
Depth	0.00-0.50	0.00-0.50	0.00-0.54	0.00-1.00	1.00-2.00	2.00-2.20	0.00-1.00	1.00-1.70	0.00-0.70	0.00-1.00		e attached n	
COC No / misc											abbrevi	ations and a	cronyms
Containers	VJT	VJT	VJT	VJT	VJT	VJT	VJT	VJT	VJT	VJT			
Sample Date	02/09/2019	02/09/2019	02/09/2019	02/09/2019	02/09/2019	02/09/2019	02/09/2019	02/09/2019	30/08/2019	30/08/2019			
Sample Type	Soil	Soil	Soil	Soil	Soil	Soil	Soil	Soil	Soil	Soil			
Batch Number	1	1	1	1	1	1	1	1	1	1			Method
Date of Receipt	05/09/2019	05/09/2019	05/09/2019	05/09/2019	05/09/2019	05/09/2019	05/09/2019	05/09/2019	05/09/2019	05/09/2019	LOD/LOR	Units	No.
TPH CWG													
Aromatics													
>C5-EC7#	<0.1 <sup>sv</sup>	<0.1 <sup>sv</sup>	<0.1 <sup>sv</sup>	<0.1	<0.1	<0.1	<0.1 <b>sv</b>	<0.1	<0.1	<0.1	<0.1	mg/kg	TM36/PM12
>EC7-EC8#	<0.1 <b>sv</b>	<0.1 <sup>sv</sup>	<0.1 <b>sv</b>	<0.1	<0.1	<0.1	<0.1 <sup>sv</sup>	<0.1	<0.1	<0.1	<0.1	mg/kg	TM36/PM12
>EC8-EC10#	<0.1 <b>sv</b>	<0.1 <b>sv</b>	<0.1 <b>sv</b>	<0.1	<0.1	<0.1	<0.1 <sup>SV</sup>	<0.1	<0.1	<0.1	<0.1	mg/kg	TM36/PM12
>EC10-EC12#	<0.2	<0.2	<0.2	<0.2	<0.2	<0.2	<0.2	<0.2	<0.2	<0.2	<0.2	mg/kg	TM5/PM8/PM16
>EC12-EC16#	<4	<4	<4	<4	<4	<4	<4	<4	<4	6	<4	mg/kg	TM5/PM8/PM16
>EC16-EC21 #	<7	<7	<7	<7	<7	<7	<7	<7	<7	66	<7	mg/kg	TM5/PM8/PM16
>EC21-EC35 #	332	<7	<7	<7	<7	<7	<7	<7	<7	334	<7	mg/kg	TM5/PM8/PM16
>EC35-EC40	237	<7	<7	<7	<7	<7	<7	<7	<7	48	<7	mg/kg	TM5/PM8/PM16
Total aromatics C5-40	569	<26	<26	<26	<26	<26	<26	<26	<26	454	<26	mg/kg	TM5/TM38/PM8/PM12/PM16
Total aliphatics and aromatics(C5-40)	719	<52	<52	<52	<52	<52	<52	<52	<52	454	<52	mg/kg	TM5/TM38/PM8/PM12/PM16
>EC6-EC10#	<0.1 <sup>SV</sup>	<0.1 <sup>sv</sup>	<0.1 <sup>sv</sup>	<0.1	<0.1	<0.1	<0.1 <sup>SV</sup>	<0.1	<0.1	<0.1	<0.1	mg/kg	TM36/PM12
>EC10-EC25	26	<10	<10	<10	<10	<10	<10	<10	<10	160	<10	mg/kg	TM5/PM8/PM16
>EC25-EC35	312	<10	<10	<10	<10	<10	<10	<10	<10	239	<10	mg/kg	TM5/PM8/PM16
MTBE#	<5 <sup>SV</sup>	<5 <sup>SV</sup>	<5 <sup>sv</sup>	<5	<5	<5	<5 <sup>sv</sup>	<5	<5	<5	<5	ug/kg	TM31/PM12
Benzene #	<5 <sup>SV</sup>	<5 <b>sv</b>	<5 <sup>SV</sup>	<5	<5	<5	<5 <b>SV</b>	<5	<5	<5	<5	ug/kg	TM31/PM12
Toluene #	<5 <b>sv</b>	<5 <b>sv</b>	<5 <sup>SV</sup>	<5	<5	<5	<5 <sup>SV</sup>	<5	<5	<5	<5	ug/kg	TM31/PM12
Ethylbenzene #	<5 <sup>SV</sup>	<5 <b>sv</b>	<5 <sup>SV</sup>	<5	<5	<5	<5 <b>SV</b>	<5	<5	<5	<5	ug/kg	TM31/PM12
m/p-Xylene #	<5 <sup>SV</sup>	<5 <sup>SV</sup>	<5 <sup>SV</sup>	<5	<5	<5	<5 <sup>SV</sup>	<5	<5	<5	<5	ug/kg	TM31/PM12
o-Xylene #	<5 <sup>SV</sup>	<5 <sup>SV</sup>	<5 <sup>SV</sup>	<5	<5	<5	<5 <sup>SV</sup>	<5	<5	<5	<5	ug/kg	TM31/PM12
PCB 28 #	<5	<5	<5	<5	<5	<5	<5	<5	<5	<5	<5	ug/kg	TM17/PM8
PCB 52#	<5	<5	<5	<5	<5	<5	<5	<5	<5	<5	<5	ug/kg	TM17/PM8
PCB 101 #	<5	<5	<5	<5	<5	<5	<5	<5	<5	<5	<5	ug/kg	TM17/PM8
PCB 118 #	<5	<5	<5	<5	<5	<5	<5	<5	<5	<5	<5	ug/kg	TM17/PM8
PCB 138 #	<5	<5	<5	<5	<5	<5	<5	<5	<5	<5	<5	ug/kg	TM17/PM8
PCB 153 #	<5	<5	<5	<5	<5	<5	<5	<5	<5	<5	<5	ug/kg	TM17/PM8
PCB 180 #	<5	<5	<5	<5	<5	<5	<5	<5	<5	<5	<5	ug/kg	TM17/PM8
Total 7 PCBs#	<35	<35	<35	<35	<35	<35	<35	<35	<35	<35	<35	ug/kg	TM17/PM8
Natural Moisture Content	6.6	6.9	6.3	9.3	12.2	8.6	6.3	13.8	4.7	17.7	<0.1	%	PM4/PM0
Moisture Content (% Wet Weight)	6.2	6.4	6.0	8.5	10.8	7.9	5.9	12.1	4.5	15.0	<0.1	%	PM4/PM0
Hexavalent Chromium #	<0.3	<0.3	<0.3	<0.3	<0.3	<0.3	<0.3	<0.3	<0.3	<0.3	<0.3	mg/kg	TM38/PM20
Chromium III	22.3	31.7	32.3	38.4	60.4	60.2	82.7	35.5	25.8	57.8	<0.5	mg/kg	NONE/NONE
Chromium III	-	-	-	-	-	-	-	-	-	-	<0.5	mg/kg	NONE/NONE
Total Organic Carbon #	0.43	0.17	0.52	0.37	0.08	0.14	0.47	0.11	0.32	7.10	<0.02	%	TM21/PM24
pH#	9.13	8.51	8.97	9.01	9.05	9.16	9.06	9.14	8.69	8.66	<0.01	pH units	TM73/PM11
Mass of raw test portion	0.0963	0.0948	0.0877	0.0973	0.105	0.0996	0.1071	0.1019	0.0942	0.1078		kg	NONE/PM17

Client Name: Ground Investigations Ireland

**Reference:** 8979-08-19

Location: Galway Docklands/Port

Contact: Barry Sexton EMT Job No: 19/14295

Report : Solid

EMT Job No:	19/14295													
EMT Sample No.	1-3	4-6	7-9	10-12	13-15	16-18	19-21	22-24	25-27	28-30				
Sample ID	WS-01	WS-02	WS-03	WS-04	WS-04	WS-04	WS-05	WS-05	WS-07	WS-09				
Depth	0.00-0.50	0.00-0.50	0.00-0.54	0.00-1.00	1.00-2.00	2.00-2.20	0.00-1.00	1.00-1.70	0.00-0.70	0.00-1.00	Please see attached notes for all			
COC No / misc											abbrevi	ations and ac	ronyms	
Containers	VJT													
Sample Date	02/09/2019	02/09/2019	02/09/2019	02/09/2019	02/09/2019	02/09/2019	02/09/2019	02/09/2019	30/08/2019	30/08/2019				
Sample Type	Soil													
Batch Number	1	1	1	1	1	1	1	1	1	1			Method	
Date of Receipt	05/09/2019	05/09/2019	05/09/2019	05/09/2019	05/09/2019	05/09/2019	05/09/2019	05/09/2019	05/09/2019	05/09/2019	LOD/LOR	Units	No.	
Mass of dried test portion	0.09	0.09	0.09	0.09	0.09	0.09	0.09	0.09	0.09	0.09		kg	NONE/PM17	